Available online at www.sciencedirect.com
SCIENCE DIRECT®
Applied Energy 81 (2005) 127–151
APPLIED ENERGY
www.elsevier.com/locate/apenergy

Modeling, numerical optimization, and irreversibility reduction of a dual-pressure reheat combined-cycle

A.M. Bassily *

Gharian University, P.O. Box 64735, Gharian, Libya

Received 26 April 2004; received in revised form 18 June 2004; accepted 26 June 2004
Available online 2 February 2005

Abstract

Optimizing the gas-turbine combined-cycle is an important method for improving its efficiency. In this paper, a dual-pressure reheat combined-cycle was modeled and optimized for 80 cases. Constraints were set on the minimum temperature-difference for pinch points (PP_m), superheat approach temperature-difference, steam-turbine inlet temperature and pressure, stack temperature, and dryness fraction at the steam-turbine's outlet. The dual-pressure reheat combined-cycle was optimized using two different methods; the direct search and the variable metric. A technique to reduce the irreversibility of the steam generator of the combined cycle was introduced. The optimized and the reduced-irreversibility dual-pressure reheat combined-cycles were compared with the regularly-designed dual-pressure reheat combined-cycle, which is the typical design for a commercial combined-cycle. The effects of varying the inlet temperature of the gas turbine (TIT) and PP_m on the performance of all cycles were presented and discussed. The results indicated that the optimized combined-cycle is up to 1% higher in efficiency than the reduced-irreversibility combined-cycle, which is 2–2.5% higher in efficiency than the regularly-designed combined-cycle when compared for the same values of TIT and PP_m. The advantages of the optimized and reduced-irreversibility combined-cycles were manifested when compared with the most efficient commercially-available combined cycle at the same value of TIT.
© 2004 Elsevier Ltd. All rights reserved.

* Present address: Frederick Institute of Technology, Department of Mechanical Engineering, 7 Yianni Street, Pallowiotissa, 1036 Nicosia, Cyprus. Fax: +357 224 38234.
E-mail address: ambassily@yahoo.com.

0306-2619/$ - see front matter © 2004 Elsevier Ltd. All rights reserved.
doi:10.1016/j.apenergy.2004.06.009

Keywords: Gas-steam combined-cycle; Gas-turbine combined-cycle; Improving efficiency; Optimized combined-cycle; Optimum combined-cycle; Optimum efficiency; Optimized cycle; Reduced irreversibility; Steam generator

Nomenclature

CC	combustion chamber
D	steam drum
h	enthalpy (kJ/kg)
$\bar{h}$	enthalpy per kmole
LHV	lower heating value (kJ/kg)
M	molecular weight (kg/kmole)
$\dot{m}$	mass-flow rate (kg/s)
P	pressure (Pa)
PP	pinch-point temperature-difference (K)
r	pressure ratio (dimensionless)
SW	specific work [kJ/kg]
T	temperature (K or °C)
TIT	gas-turbine's inlet-temperature (K)
TOT	gas-turbine's outlet-temperature (K)
X	steam dryness-fraction (dimensionless)
y	mole fraction
α	reheat pressure ratio
η	efficiency (dimensionless)
δT	temperature difference (K)
γ	principal specific-heats ratio (dimensionless)

Subscripts

a	air
c	cooling
ccycle	combined cycle
com	compressor
f	fuel
g	gas
gcycle	gas cycle
i	point number i, or component number i
m	minimum
s	steam
sD_1	dry steam for drum 1
seDi	evaporation for steam of drum number i
sta	stack
stih	steam at the inlet of the high-pressure turbine

دریافت فوری ← متن کامل مقاله

ISIArticles
مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات