


# Accepted Manuscript

On the effect of curing time and environmental exposure on impregnated carbon Fabric Reinforced Cementitious Matrix (CFRCM) composite with design considerations

A. Nobili, C. Signorini



PII: S1359-8368(16)32122-9

DOI: [10.1016/j.compositesb.2016.12.022](https://doi.org/10.1016/j.compositesb.2016.12.022)

Reference: JCOMB 4777

To appear in: *Composites Part B*

Received Date: 29 September 2016

Revised Date: 16 November 2016

Accepted Date: 4 December 2016

Please cite this article as: Nobili A, Signorini C, On the effect of curing time and environmental exposure on impregnated carbon Fabric Reinforced Cementitious Matrix (CFRCM) composite with design considerations, *Composites Part B* (2017), doi: 10.1016/j.compositesb.2016.12.022.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

On the effect of curing time and environmental exposure on impregnated Carbon Fabric Reinforced Cementitious Matrix (CFRCM) composite with design considerations

A. Nobili<sup>a,\*</sup>, C. Signorini<sup>b</sup>

<sup>a</sup>*Dipartimento di Ingegneria Enzo Ferrari, via Vignolese 905, 41125 Modena, Italy*

<sup>b</sup>*Dipartimento di Scienze e Metodi dell'Ingegneria, via Amendola 2, 42122 Reggio Emilia, Italy*

---

**Abstract**

This paper investigates the effect of curing time and aggressive environmental exposure on the mechanical performance of impregnated Carbon Fabric Reinforced Cementitious Matrix (CFRCM) composite. Following the recently published IIC-ES AC434 guidelines, saltwater, distilled water, alkali and acid resistance are investigated together with freeze-thaw cycles. Mechanical characterization is based on tensile uni-axial tests under deformation control of rectangular-base prismatic specimens. 28- and 60-day curing times are considered for the control environment as well as for saltwater and alkali resistance. Deformation is monitored via digital acquisition. Besides uni-axial tests, experimental results comprise optical and scanning electron microscopy, crack pattern analysis and failure mechanism assessment. Focus is set on the determination of the design limits for the composite system at failure for the tested environments and curing times. In particular, a comparison is drawn with established design criteria already coded for FRP systems, which introduce the concept of safety (or partial) factors. Environmental conversion factors are also defined and calculated on a statistical basis in a twofold manner, as a mean to determine the design strain and strength limits of exposed specimens from the control (unex-

---

\*Corresponding author

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات