



ELSEVIER

Available online at [www.sciencedirect.com](http://www.sciencedirect.com)

SCIENCE @ DIRECT®

Computers and Electrical Engineering 31 (2005) 303–333

Computers and  
Electrical Engineering

[www.elsevier.com/locate/compeleceng](http://www.elsevier.com/locate/compeleceng)

## Fixed channel assignment using new dynamic programming approach in cellular radio networks

S. Alireza Ghasempour Shirazi<sup>a,1</sup>, Hamidreza Amindavar<sup>b,\*</sup>

<sup>a</sup> ICT Faculty—Information and Communications Technology, P.O. Box 16315-746, Tehran, Iran

<sup>b</sup> Amirkabir University of Technology, Electrical Engineering Department, Hafez Avenue, 15914 Tehran, Iran

Received 29 September 2003; received in revised form 5 April 2005; accepted 5 April 2005

Available online 25 August 2005

---

### Abstract

In this paper, we propose a new approach to the fixed channel assignment problem by modifying the dynamic programming technique. This new strategy extends the already known dynamic programming so that the channel assignment solutions can be obtained. There is no need to have an initial random solution for convergence. One of the questions in the fixed channel assignment is the minimum bandwidth, which is usually unknown; the new strategy can obtain this lower bound. Parallel processing can be implemented over the proposed algorithm. The existing fixed channel assignment methods do not have all these in one place. The performance of modified dynamic programming (MDP) is evaluated by computer simulation, applied to seven well-known benchmark problems on channel assignment. The channel assignment strategies results shows that required bandwidths of modified dynamic programming are closely match or sometimes better than the algorithms that we have investigated.

© 2005 Elsevier Ltd. All rights reserved.

---

\* Corresponding author. Tel.: +98 21 6454 3332; fax: +98 21 640 6469.

E-mail addresses: [ghasempour@ictfaculty.ir](mailto:ghasempour@ictfaculty.ir) (S. Alireza Ghasempour Shirazi), [hamidami@aut.ac.ir](mailto:hamidami@aut.ac.ir) (H. Amindavar).

<sup>1</sup> Tel.: +98 21 465 4819; fax: +98 21 465 9665.

## 1. Introduction

The appearance of cellular mobile communication systems and their rapid growth due to the portability and the availability of these systems provided an important alternative in the field of wireless mobile communications. The increasing demand of new services in this field, however, is in contrast to the capacity constraints inherent in the current communication systems. Hence, the use of techniques, which are capable of ensuring that the frequency spectrum assigned for use in mobile communications will be better utilized, is gaining an ever-increasing importance.

This makes the task of channel assignment more and more crucial [1]. The channel assignment problem (CAP) in this paper is based on a common model. The service area of the system is divided into a number of hexagonal cells. Every user is located in one cell. When a user requests a call in this system, a channel is assigned to that user to provide the communication service. This channel assignment must satisfy the electromagnetic compatibility (EMC) constraints to avoid the radio interference between channels. Three types of EMC constraints have usually been considered in CAP.

1. The co-channel constraint (CCC): The same channel cannot be assigned to cells that have a certain distance from each other.
2. The adjacent channel constraint (ACC): Adjacent channels cannot be assigned to adjacent cells simultaneously. In other words, any pair of channels in adjacent cells must have specified distance. Note that the distance indicates the difference in the channel domain.
3. The co-site constraint (CSC): Any pair of channels in a cell must have a specified distance. This distance is usually larger than necessary distance for ACC.

The channel assignment problem (CAP) is then to allocate channel to every requested call in a cellular radio network subject to the above three EMC constraints such that the required bandwidth is minimized.

Channel assignment is generally classified into fixed and dynamic. In fixed channel assignment (FCA), channels are nominally assigned to cells in advance according to the predetermined estimated traffic intensity. In dynamic channel assignment (DCA), channels are assigned dynamically as calls arrive. The latter method makes cellular systems more efficient particularly if the traffic distribution is unknown or changes with time, but has the disadvantage of requiring more complex control and is generally time consuming [2]. Normally, DCA gives better performance than FCA except under heavy traffic load condition, where FCA outperforms DCA [3]. Since heavy traffic load is expected in the future generation of cellular radio networks, an efficient FCA scheme that can provide high spectrum usage efficiency is desired. The FCA problem has been studied extensively for the past three decades. A comprehensive summary of the work done before 1980 can be found in [4]. Various extensions or combinations of the above two schemes have been discussed in the literature. The most basic are the hybrid channel assignment (HCA) and the borrowing channel assignment (BCA). In HCA, the set of channels of the cellular system is divided into two subsets, from which the one uses FCA and the other DCA. In BCA, the channel assignment is initially fixed. If there are incoming calls for a cell whose channels are all occupied, the cell borrows channels from its neighboring cells and thus call blocking is prevented [5,6].

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات