

# Dynamic programming and Lagrange multipliers for active relaxation of resources in nonlinear non-equilibrium systems

Stanislaw Sieniutycz\*

*Warsaw University of Technology, Faculty of Chemical and Process Engineering, Department of Process Separation,  
1 Waryńskiego Street (Room 232), 00-645 Warsaw, Poland*

Received 11 July 2007; received in revised form 21 January 2008; accepted 4 February 2008

Available online 9 February 2008

---

## Abstract

In power production problems maximum power and minimum entropy production and inherently connected by the Gouy–Stodola law. In this paper various mathematical tools are applied in dynamic optimization of power-maximizing paths, with special attention paid to nonlinear systems. Maximum power and/or minimum entropy production are governed by Hamilton–Jacobi–Bellman (HJB) equations which describe the value function of the problem and associated controls. Yet, in many cases optimal relaxation curve is non-exponential, governing HJB equations do not admit classical solutions and one has to work with viscosity solutions. Systems with nonlinear kinetics (e.g. radiation engines) are particularly difficult, thus, discrete counterparts of continuous HJB equations and numerical approaches are recommended. Discrete algorithms of dynamic programming (DP), which lead to power limits and associated availabilities, are effective. We consider convergence of discrete algorithms to viscosity solutions of HJB equations, discrete approximations, and the role of Lagrange multiplier  $\lambda$  associated with the duration constraint. In analytical discrete schemes, the Legendre transformation is a significant tool leading to original work function. We also describe numerical algorithms of dynamic programming and consider dimensionality reduction in these algorithms. Indications showing the method potential for other systems, in particular chemical energy systems, are given.

© 2008 Elsevier Inc. All rights reserved.

*Keywords:* Resources; Power generation; Radiation; Dynamic programming

---

## 1. Introduction

In this paper we consider analytical and computational aspects of energy limits in dynamical systems propelled by nonlinear fluids that are restricted in their amount or flow, and, as such, play role of resources. In practical processes of engineering and technology a resource is a useful, valuable substance of a limited amount or flow. Value of the resource can be quantified thermodynamically by specifying its exergy, a

---

\* Tel.: +48 228 256340; fax: +48 228 251440.

E-mail address: [sieniutycz@ichip.pw.edu.pl](mailto:sieniutycz@ichip.pw.edu.pl)

## Nomenclature

$a$	temperature power exponent in kinetic equation
$c$	specific heat ( $\text{J g}^{-1} \text{K}^{-1}$ , $\text{J m}^{-3} \text{K}^{-1}$ , $\text{J mol}^{-1} \text{K}^{-1}$ )
$D^n, \tilde{D}^n$	generalized profit and gauge profit at stage $n$
$G$	gauge function
$\dot{G}$	resource flux ( $\text{g s}^{-1}$ , $\text{mol s}^{-1}$ )
$\mathbf{f}$	rate vector with components $f_1 \dots f_k \dots f_s$
$f_0$	intensity of generalized profit
$H$	Hamiltonian function
$l_0$	Lagrangian, intensity of generalized cost
$R$	minimum performance function ( $\text{J}$ , or $\text{J mol}^{-1}$ )
$S$	entropy ( $\text{J K}^{-1}$ )
$T$	variable temperature of resource fluid ( $\text{K}$ )
$T^n$	temperature after stage $n$ ( $\text{K}$ )
$T^e$	constant temperature of environment ( $\text{K}$ )
$T'$	Carnot temperature control ( $\text{K}$ )
$\dot{T}$	$u$ rate of controlling of $T$ in time $\tau$ ( $\text{K}$ )
$t$	time ( $\text{s}$ )
$\mathbf{u}$	control vector
$u$	temperature rate control, $dT/d\tau$ ( $\text{K}$ )
$V$	maximum performance function ( $\text{J}$ , or $\text{J mol}^{-1}$ )
$W$ and $\dot{W}$	work and power ( $\text{J}$ , $\text{J s}^{-1}$ )
$\mathbf{x}$	state vector
$\tilde{\mathbf{x}}$	enlarged state vector including time
$z_k$	adjoint variable

### Greek symbols

$\beta$	coefficient, frequency constant ( $\text{s}^{-1}$ )
$\lambda$	Lagrange multiplier, time adjoint
$\eta$	first-law efficiency ( $-$ )
$\theta$	time interval ( $\text{s}$ , $-$ )
$\Phi$	factor of machine irreversibility ( $-$ )
$\zeta$	intensity factor ( $-$ )
$\tau$	nondimensional time or number of heat transfer units ( $x/H_{\text{TU}}$ ) ( $-$ )

### Subscripts

$k$	$k$ th state variable
$m$	molar flow
$1, 2$	first and second fluid
$*$	modified cost or profit

### Superscripts

$e$	environment
$i$	initial state
$n-$	stage number
$f$	initial state
$'$	modified quantity

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات