



Structural behaviour of a GFRP-concrete hybrid footbridge prototype: Experimental tests and numerical and analytical simulations



José A. Gonilha*, João R. Correia, Fernando A. Branco

Department of Civil Engineering, Architecture and Georesources, Instituto Superior Técnico/ICIST, University of Lisbon, Av. Rovisco Pais 1, 1049-001 Lisboa, Portugal

ARTICLE INFO

Article history:

Received 11 October 2013

Revised 4 December 2013

Accepted 11 December 2013

Available online 9 January 2014

Keywords:

Glass fibre reinforced polymer (GFRP)

Steel fibre reinforced self-compacting

concrete (SFRSCC)

Hybrid structure

Footbridge

Prestress

Flexure

Experimental tests

Modelling

ABSTRACT

Glass fibre reinforced polymer (GFRP) pultruded profiles are being increasingly used in the construction industry since the last few decades. The high potential of GFRP profiles for structural applications stems from their high strength, low self-weight and corrosion resistance. In opposition, the high deformability, the susceptibility to instability phenomena and the lack of specific design codes have been hindering a wider use of these advanced composite materials. Several hybrid systems in which GFRP materials are combined with traditional materials, namely concrete, have been proposed in order to overcome the aforementioned limitations of the GFRP material. This paper presents experimental, analytical and numerical investigations about the flexural behaviour of a GFRP-concrete hybrid footbridge prototype comprising two I-shaped GFRP main girders and a thin steel fibre reinforced self-compacting concrete (SFRSCC) deck. With the aim of limiting the structure's deformability, the footbridge features an external prestress system consisting of two ordinary steel rebars screwed tight to the structure at the support sections. A small-scale footbridge prototype, 6.0 m long and 2.0 m wide, was built and tested in a 5.5 m simply supported span. The experimental programme included (i) serviceability tests, with and without the application of the external prestress system, and (ii) failure tests. Results of flexural tests proved the feasibility and advantages of the structural concept proposed: the judicious combination of GFRP and SFRSCC enabled the development of a lightweight, high performance and relatively inexpensive structural system for footbridges; furthermore, the external prestress system was very effective in limiting deflections. The analytical and numerical models developed in this study were able to predict with good accuracy (i) the linear elastic behaviour of the structure up to failure, (ii) the effects of the external prestress, and (iii) the failure mode and strength, proving to be accurate tools for the design of GFRP-concrete structural solutions.

© 2013 Elsevier Ltd. All rights reserved.

1. Introduction

In the last few decades, the use of fibre reinforced polymer (FRP) materials in general, and of glass fibre reinforced polymer (GFRP) pultruded profiles in particular, has found a significant increase in civil engineering structural applications. In fact, these materials have high potential for both building and bridge structural applications owing to their high strength, low self-weight, chemical resistance, ease of installation and electromagnetic transparency [1–3]. However, the lack of specific standards dealing with the various aspects of the design, the brittle failure, the high deformability and the susceptibility to instability phenomena, which often govern design and seldom allow the full exploitation of the materials' resistance [4–6], have been delaying the widespread use of these materials [7–10].

Several hybrid structural systems combining GFRP elements with traditional materials have been proposed in order to overcome the aforementioned limitations while maintaining the main attractiveness of advanced composite structures. In those systems, the careful combination of GFRP with concrete in flexural members has proven to be particularly effective, namely in reducing short- and long-term deformability and in delaying instability phenomena (e.g. [11–19]).

The research presented in this paper is part of a broader research project – PONTALUMIS – a collaborative study between Instituto Superior Técnico (IST), Minho University (UM) and composites manufacturer ALTO, *Perfis Pultrudidos, Lda*. This project aims at developing a lightweight, durable and maintenance-free hybrid footbridge made of two I-shaped GFRP pultruded profiles acting as main girders and a steel fibre reinforced self-compacting concrete (SFRSCC) deck. In order to fully understand the feasibility and structural behaviour of the structural system proposed, the research project included the construction of a small-scale prototype, with a length of 6.0 m, approximately half of the length of the

* Corresponding author. Tel./fax: +351 2184 17000/99242.

E-mail address: jose.gonilha@tecnico.ulisboa.pt (J.A. Gonilha).

Nomenclature

Symbol	Description	Symbol	Description
a, b	geometrical parameters of the 4-point bending load configuration	M_F	bending moment due to the applied load F
b_p	width of the GFRP profiles' flanges	M_{max}	maximum bending moment
d	distance between the theoretical support and the rotation point of the rebars	M_u	ultimate bending moment
e	eccentricity of the prestress rebars with respect to NA	M_{SW}	bending moment due to the self-weight
f_{au}	tensile strength of the epoxy adhesive	NA	neutral axis position measured from the top fibre of the cross-section
f_{bk}	characteristic tensile strength of the stainless steel bolts	P	prestress force
f_{cm}	compressive strength of the SFRSCC	S	shear strength in the plane 1–2
f_{cr}	tensile cracking strength of the SFRSCC	$V(x)$	shear force at position x
f_{mu}	compressive strength of the epoxy mortar	V_F	shear force due to the applied load F
$f_{tu,L}$	tensile strength of the GFRP for the longitudinal direction	V_{SW}	shear force due to the self-weight
h_c	thickness of the SFRSCC slab	V_u	ultimate shear force
h_p	height of the GFRP profiles	X	axial strength in direction 1
h_t	total height of the cross-section	Y	axial strength in direction 2
i	number of element	$\delta(x)$	deflection at position x
kA	Timoshenko shear area	δ_{ms}	average midspan deflection
l	free length of the rebars	δ_{ms1-2}	midspan deflection measurement positions
t_f	thickness of the GFRP profiles' flanges	δ_{ms-u}	midspan deflection at failure
t_w	thickness of the GFRP profiles' webs	$\delta_p(x)$	upwards deflection at position x caused by the prestress load P
x	longitudinal development of the structure	ε_{c1-3}	midspan strain measurement positions on the SFRSCC
z	vertical distance to z_g	ε_{f1-2}	midspan strain measurement positions on the GFRP flanges
z_g	neutral axis height with respect to the mid-line of the GFRP bottom flanges	ε_{w1-2}	midspan strain measurement positions on the GFRP webs
z_{gi}	vertical position of the stiffness centre of element i	θ_L	rotation of the support section due to vertical loads
A_i	area of element i	θ_P	rotation of the support section due to prestress loads
A_s	area of the steel rebars	θ_T	total rotation of the support section
A_w	area of the GFRP webs	ρ	volumetric weight
E_a	elasticity modulus in tension of the epoxy adhesive	$\sigma(x,z)$	axial stress at position x, z
E_c	elasticity modulus in compression of the SFRSCC	σ_1	axial stress in direction 1
E_i	elasticity modulus of element i	σ_2	axial stress in direction 2
El	flexural stiffness of the cross-section	σ_F	axial stress due to the applied load F
$E_{L,t}$	elasticity modulus in tension of the GFRP for the longitudinal direction	σ_L	axial stress in longitudinal direction
E_m	elasticity modulus in compression of the epoxy mortar	σ_{SW}	axial stress due to the self-weight
E_s	elasticity modulus of steel	σ_T	axial stress in transverse direction
$E_{T,c}$	elasticity modulus in compression of the GFRP for the transverse direction	$\tau(x,z)$	shear stress at position x, z
F	applied load in the 4-point bending load configuration	τ_{12}	shear stress in the plane 1–2
$F_{cu,L}$	compressive strength of the GFRP for the transverse direction	τ_F	shear force due to the applied load F
F_u	failure load	τ_{LT}	shear stress in the plane defined by the longitudinal and transverse directions
G	shear modulus	τ_{mu}	shear strength of the epoxy mortar
G_{LT}	shear modulus of the GFRP	τ_{SW}	shear stress due to the self-weight
K	average midspan stiffness	$\tau_{u,LT}$	in-plane shear strength of the GFRP
L	Span	ν	Poisson's ratio of the SFRSCC
$M(x)$	bending moment at position x	χ	curvature of the cross-section
		Δ	elongation of the rebars
		ΔP	additional force on the rebars caused by the vertical loads

full-scale prototype. Previous studies were already performed in order to investigate the structural behaviour of this small-scale prototype, namely in what concerns the following aspects: (i) performance of different shear connection systems used at the GFRP–SFRSCC interface [20]; (ii) modal (dynamic) identification [21]; (iii) dynamic response of the footbridge under pedestrian loads [6]; and (iv) creep behaviour of the footbridge under sustained loads [19].

This paper presents experimental, analytical and numerical investigations about the short-term static behaviour up to failure of the hybrid GFRP–SFRSCC small-scale footbridge prototype. The remainder of the paper is organised as follows. Section 2 describes

the underlying structural concept of the footbridge prototype and details its geometry. Section 3 presents the experimental programme, which included the construction of the footbridge prototype, material characterisation tests on the constituent materials and 4-point bending flexural tests, which aimed at evaluating both the serviceability and failure responses of the prototype, as well as to assess the efficacy of an external prestress system in limiting the deformability of the hybrid structure. Sections 4 and 5 present analytical and numerical simulations of the structural behaviour of the footbridge, in which simple analytical formulae and a three-dimensional finite element model, respectively, were used to predict the serviceability and failure responses of the hybrid footbridge structure.

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات