



24th DAAAM International Symposium on Intelligent Manufacturing and Automation, 2013

Calibration of an Industrial Robot using a Stereo Vision System

Marko Švaco*, Bojan Šekoranja, Filip Šuligoj, Bojan Jerbić

*University of Zagreb, Faculty of Mechanical Engineering and Naval Architecture, Department of Robotics and Production System Automation,
Ivana Lučića 5, 10000 Zagreb, Croatia*

Abstract

Industrial robots have very good repeatability but still lack good absolute accuracy. The main reason is difference between the ideal robot kinematic model integrated in the robot controller and actual robot parameters. A method for identifying certain parameters of the robot model has been proposed. A noncontact method using a stereovision system attached to the robot arm is utilized for providing measurements of calibration points in space. Points are represented as spheres which localized by the stereo vision system project a circle in two image capture planes independent of the viewing angle. Spatial coordinates of each sphere center are acquired in different robot configurations. From these readings errors of robot absolute positioning are measured. The standard Denavit-Hartenberg (DH) notation is used when the modified model parameters containing joint encoder offset values are directly input to the robot controller. Calibration experiments carried out on a KUKA KR 6 R900 industrial robot show improved accuracy results. The maximum positioning error around calibration points was decreased from 3.63 mm prior to calibration, to 1.29 mm after the calibration procedure.

© 2014 The Authors. Published by Elsevier Ltd. Open access under [CC BY-NC-ND license](https://creativecommons.org/licenses/by-nc-nd/4.0/).
Selection and peer-review under responsibility of DAAAM International Vienna

Keywords: Robot calibration; absolute accuracy

1. Introduction

Industrial robots have a very broad field of application ranging from assembly, manufacturing, and other technologies. Industrial robots mostly deal with processes in known and structured environments where robot motion is preprogrammed and executed, continuously repeating the same paths and motions. For this reason industrial robots are designed and manufactured to provide very high repeatability for successful execution of predefined tasks.

* Corresponding author. Tel.: +385 1 6168 380; fax: + 385 1 6156 940.
E-mail address: marko.svaco@fsb.hr

The aspect, in which industrial robots are still not able to provide satisfactory results, when delivered to end customers, is absolute accuracy. In 6 degree of freedom (DOF) serial link manipulators [1] this problem is emphasized. As every industrial robot is manufactured in a certain tolerance range there are no two identical mechanical units. On the other hand each robot controller utilizes the same control model with ideal DH [2] parameters (link lengths, offsets, twist, etc.). For this reason there always exists a certain error describing the difference between the ideal position in the robot model and the actual position of the robot in some reference frame.

Research in the field of robot calibration shows different calibration methods and algorithms which evaluate DH parameters of the robot model or describe novel kinematic robot models with additional parameters for improving accuracy results. In [3] a calibration method is proposed utilizing a virtual closed kinematic chain method. A laser spot is projected on a distant plane and small robot motions are magnified. A calibration method for identification of 36 independent parameters of a robot arm is described in [4]. Authors apply a principle of moving the robot endpoint around spherical shells centered on a fixed point, collect data and perform identification of robot kinematic parameters. Another calibration approach utilizing cooperative coevolutionary networks and pseudoerror theory is described in [5]. Measurement methods in robot calibration range from theodolite [6], laser beam projection [3], 2D machine vision [7], portable coordinate measuring machines [8] and other.

From the robot kinematic model overview industrial robot calibration methods can roughly be distinguished in three categories:

- Error registration – the robot is viewed as a black box where compensation factors and values are given for every robot pose
- Static calibration – identification of time invariant robot parameters
- Dynamic calibration – identification of robot motion parameters

Duelen and Schroer [9] suggest that all parameters of the kinematic robot model could be identified only by measuring the position of a certain point of the robot end effector. Applying this principle, in this research a static noncontact closed chain calibration method using stereovision is presented for evaluating robot kinematic parameters that can be embedded directly in KUKA robot controllers. With this approach the control hierarchy and structure of a robotic system is left intact and the usability of an industrial robot is not altered. In following sections the experimental setup is described, methods and algorithms are presented and preliminary results are discussed.

2. System setup

The system consists of a 6 DOF KUKA KR 6 R900 robot arm with declared repeatability of ± 0.03 mm and payload of 6 kg. DH parameters of the robot are depicted in Table 1.

Table 1. Original values of DH robot parameters.

	d (mm)	θ (deg)	a (mm)	α (deg)
Link 1	400	θ_1	25	90
Link 2	0	θ_2	455	0
Link 3	0	θ_3	35	90
Link 4	420	θ_4	0	-90
Link 5	0	θ_5	0	90
Link 6	80	θ_6	0	180

The robot has a tool changing device which allows flexible automatic tool exchange. The stereo vision system (as shown in Fig.1 a) consists of two perpendicular CCD cameras which form a virtual robot tool center point (TCP). The two CCD cameras have macro lenses and allow high magnification of the viewed object. For the calibration purpose a black polymer sphere was used. One pixel is roughly mapped to 0.05mm and the vision system allows high resolution and accurate readings of sphere center.

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات