



Research paper

Experimental and simulation study on the air side thermal hydraulic performance of automotive heat exchangers



Y.Y. Liang*, C.C. Liu, C.Z. Li, J.P. Chen

Institute of Refrigeration and Cryogenics, Shanghai Jiao Tong University, No. 800 Dongchuan Road, Shanghai 200240, China

HIGHLIGHTS

- Automotive heat exchangers with different fin heights were examined experimentally.
- Distributed parameter models for automotive heat exchangers were developed.
- Models were validated by comparing the results to those derived from Coil Designer.
- Feasibility study was made on correlations for louvered surface.

ARTICLE INFO

Article history:

Received 23 October 2014

Accepted 2 May 2015

Available online 19 May 2015

Keywords:

Automotive
Heat exchanger
Louvered fin
Correlation
Comparison

ABSTRACT

Flat tube heat exchangers with louvered fins were applied in order to meet the performance requirements and compactness in automotive air conditioning systems. Experimental and simulation study focusing on the air side thermal hydraulic performance of automotive heat exchangers were performed in this article. Test results showed that the heat capacity of a condenser with 5.4 mm height louvered fins can be 3.0%–8.6% higher than the 8 mm fin height condenser of the same size. Automotive evaporator can have 9.3% volume reduction by using short louvered fins while retain the same cooling capacity. Distributed parameter models were developed for automotive heat exchangers and effectiveness NTU method was used to calculate the heat capacity. The models were validated by comparing the results to those calculated *via* Coil Designer 3.6. Verification has been done for several well-known correlations used for the calculation of thermal hydraulic performance of wet and dry louvered surfaces. The correlations were evaluated by comparing calculations with test data of 24 different specimens under typical automotive heat exchanger working conditions. It was concluded that the existing correlations can give satisfactory predictions for heat capacity of condensers and evaporators, and air side pressure loss of condenser. However, further study on the friction characteristic of wet louvered fins is still needed.

© 2015 Elsevier Ltd. All rights reserved.

1. Introduction

There are high requirements on compactness and good performance of heat exchangers (HXs) for limited space applications, such as automotive air conditioning systems. In recent years, increasingly restrictive emission regulations and demand for energy saving has drawn intensive attention, as well as the passengers' requirements for thermal comfort. One effective solution is to use high performance HXs. The most commonly used methods for developing high performance HXs are increasing heat transfer area

by increasing fin density and strengthening turbulence by using enhanced fins like louvered, wavy fins. Round tube-and-fin, laminated and serpentine HXs have also been used in automotive air conditionings. In the last century, parallel flow HXs consist of louvered fins brazed to multi-port flat tubes were developed, with merits including compactness, low refrigeration charge, light weight and low cost. They have replaced traditional HXs and were widely applied in the automotive industry.

Simulation model has been considered as an effective tool in design and optimization of HX for cutting experimental work and the manufacturing cost of samples, and has the ability to clarify some parameters that can't be measured directly during tests such as refrigerant quality and heat transfer coefficient. Models used to describe the HXs can be mainly divided into three types: lumped

* Corresponding author. Tel.: +86 18801970503; fax: +86 02134206087.
E-mail address: yuanyuan1989@yeah.net (Y.Y. Liang).

Nomenclature	
A	surface area (m^2)
C	specific heat ($\text{J kg}^{-1} \text{K}^{-1}$)
c_p	specific heat at constant pressure ($\text{J kg}^{-1} \text{K}^{-1}$)
D_h	hydraulic diameter of air passage between fins (m)
f	friction factor
F_d	fin width (m)
F_h	fin height (m)
F_l	fin length (m)
G	mass flux ($\text{kg m}^{-2} \text{s}^{-1}$)
h	heat exchange coefficient ($\text{W m}^{-2} \text{K}^{-1}$)
i	moist air enthalpy (J kg^{-1})
j	colburn factor
k	thermal conductivity ($\text{W m}^{-1} \text{K}^{-1}$)
l	length (m)
L_l	louver length (m)
L_p	louver pitch (m)
m	mass flow rate (kg s^{-1})
N_{bl}	number of louver banks
N_p	number of ports in every flat tube
NTU	number of heat transfer units
Ph	port height (m)
P_w	port width (m)
Q	heat capacity (W)
Re	Reynolds number
t	temperature ($^{\circ}\text{C}$)
T_l	tube length (m)
T_p	tube pitch (m)
T_w	tube width (m)
U	overall heat transfer coefficient ($\text{W m}^{-2} \text{K}^{-1}$)
X_i	independent measurement
y_w	thickness of water film (m)
<i>Greek letters</i>	
δ	thickness (m)
ρ	density (kg m^{-3})
ε	effectiveness
η	fin efficiency (–)
θ	louver angle ($^{\circ}$)
ΔP	pressure drop (Pa)
<i>Subscripts</i>	
a	air/air side
f	fin
i	inside
in	inlet
o	outside
r	refrigerant/refrigerant side
s	saturation
t	tube
w	water
wet	wet condition

parameter model, zone model and distributed parameter model [1]. The lumped model and zone model are simple and usually applied in cases where quick calculation speed are required. The distributed model divides the HX into several calculation cells, which has the ability to look into the geometric details (including manifolds, flow arrangement, fins and the tubes) and has higher accuracy. So it is commonly used for HX performance prediction.

There are several factors that affect the model's accuracy: (a) refrigerant distribution, (b) air distribution, and (c) air side and tube side heat transfer coefficients. The commonly used perforated baffles can effectively enhance the uniformity of flow distribution in headers, but neglecting the pressure drop in header will lead to unreasonable calculation of mass flow rate. Tuo and Bielskus [2] found model which reflects refrigeration distribution provides better prediction for cooling capacity and outlet superheat. Some more researchers have studied and proposed methods to calculate flow distribution for HXs [3–6]. And non-uniform air flow has been a necessary consideration in models for HXs [7,8]. In a HX model, the most important source of uncertainty comes from the correlations employed for the air and refrigerant side heat transfer coefficients [9]. Various correlations for condensing and evaporating have been proposed to predict the two phase heat transfer rate. Some widely used correlations were evaluated depending on their deviation to test data [9,10]. Actually, for HXs used in vapor compression refrigeration systems, the air side thermal resistance accounts for more than 80% of the overall thermal resistance, so the calculation of air side heat transfer coefficient is more critical to the model's accuracy.

The study on the thermal hydraulic performance of louvered surface has been a hot topic [11–22]. Davenport [11] studied 32 louvered surfaces and found fin performance is more relevant to Reynolds number based on louver pitch than that based on the

hydraulic diameter of air passage between fins. Study from Achai-chia and Cowell [12] showed the air flow turns from louver-directed to duct-directed as the Reynolds number reduces. Lots of correlations can perfectly predict performance based on their own test data, but they fail to offer accurate prediction for test data from other researchers. In light of this, Chang and Wang [13,14] collected data from 9 independent laboratories, and regression analysis was performed to obtain generalized correlations for louvered fins. Based on the most comprehensive experimental database in the literature, including 1030 heat transfer and 1270 pressure drop measurements, Park and Jacobi [17] tried to develop new form of formulas that can reflect all parametric effects found in database. Correlations under wet condition for louvered fins are limited. Kim and Bullard [18] performed an experimental study for 30 louvered fin HXs under wet conditions. They found that the sensitive heat transfer coefficient is smaller than that for the dry surface at low air velocity for large louver angle and fin pitch, while it is larger at high face velocity. Park and Jacobi [19] developed two forms of empirical correlations for wet condition, one uses wet-surface multipliers and the other are standalone j - and f -factors. Geometrical parameters of studied louvered fins from related researchers are listed in Table 1. Schematic diagrams of a typical automotive evaporator and constructions of louvered fin are shown in Fig. 1.

A typical louvered fin has nine or more geometrical parameters relevant to their air side performance, which means a large and diverse database is imperative to obtain accurate and reliable correlations for louvered fins. To guarantee the generality of correlations, generally, all test data are used to develop formulas, i.e., the same database is used for development and validation of new correlations, it is somewhat less convincing. Automotive HXs have their own geometrical features such as low fin height and small fin width. The fin height used in automotive HXs is usually less than

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات