



A proposal for off-grid photovoltaic systems with non-controllable loads using fuzzy logic



Imene Yahyaoui ^{a,b,*}, Souhir Sallem ^b, M.B.A. Kamoun ^b, Fernando Tadeo ^a

^a Industrial Engineering School, University of Valladolid, Spain

^b Unité de Commande de Machines et Réseaux de Puissance CMERP-ENIS, University of Sfax, Tunisia

ARTICLE INFO

Article history:

Available online 22 October 2013

Keywords:

Renewable energy
Energy management
Fuzzy logic algorithm
Battery protection

ABSTRACT

A fuzzy-logic based methodology is proposed and evaluated for energy management in off-grid installations with photovoltaic panels as the source of energy and a limited storage capacity in batteries. The decision on the connection or disconnection of components is based on fuzzy rules on the basis of the Photovoltaic Panel Generation measurement, the measured power required by the load, and the estimation of the stored energy in the batteries (this last is obtained from the estimation of the Depth-of-Discharge). The algorithm aims to ensure the system's autonomy by controlling the switches linking the system components with respect to a multi-objective management criterion developed from the requirements (supply of the load, protection of the battery, etc.). Detailed tests of the proposed system are carried out using data (irradiation, temperature, power consumption, etc.) measured in a household at the target area at several days of the year. The results demonstrate that the proposed approach achieves the objectives of system autonomy, battery protection and power supply stability. Compared with a basic algorithm, the proposed algorithm is not sensitive to sudden changes in atmospheric parameters and avoids overcharging the battery.

© 2013 Elsevier Ltd. All rights reserved.

1. Introduction

The demand for electrical energy supply systems in isolated areas is increasing around the world, for water pumping [1], desalination [2] and supplying remote dwellings with electricity [3]. This motivates the development of novel energy management methodologies to balance production with demand. Among the renewable energy sources that are being installed, photovoltaic panels (PVPs) is probably the most frequent, since it offers many advantages such as low maintenance costs, no polluting, and no noise.

The main disadvantage is that the electricity is produced only during the day, so if the electrical load cannot be fully controlled to balance with the electricity production, the use of batteries is essential.

These off-grid PVP-based systems, require specific solutions that are being researched, focusing on system modeling [4], PVP sizing [5,6], optimization [7], Maximum Power Point Tracking

(MPPT) [8], etc. These issues are mainly deliberated in the literature and efficient standard tools have been advanced [9].

Fuzzy Management Algorithms (FMAs) have previously shown to offer adequate energy management of the photovoltaic systems [10]. Thus, starting from a preliminary study presented in [11], the management algorithm is refined here, with improved models, is generalized for generic non-adaptable loads, and its performance is demonstrated using measured data of a household in the target area.

Thus, this paper presents the development and tests of a management strategy for off-grid PVP-based systems that is advanced (in the sense that it is based on considering several measurements to find on-line a compromise between conflicting objectives), that can be adapted to different configurations and could be implemented using off-the-shelf hardware and software. To do so, Mamdani-type fuzzy logic is used within the management algorithm as it is simple to learn for operators with little technical training [12] and can be implemented using standard components, such as Programmable Industrial Controllers [13].

Following previous works [11], the estimated power produced by the photovoltaic panel is used by the algorithm. This estimation is used to decide when to connect the components of the system using a fuzzy-rules algorithm. The decisions taken ensure the autonomy of the system, the correct charge/discharge of the

* Corresponding author at: Unité de Commande de Machines et Réseaux de Puissance CMERP-ENIS, University of Sfax, Tunisia. Tel.: +216 96 62 25 25; fax: +216 78 68 00 25.

E-mail addresses: i.ma.nova@hotmail.fr, imene@autom.uva.es (I. Yahyaoui), souhirsallem@gmail.com (S. Sallem), mba.kamoun@enis.rnu.tn (M.B.A. Kamoun), fernando@autom.uva.es (F. Tadeo).

Nomenclature

a	temperature coefficient	$M_{1,2,3,4,5,6}$	function modes 1, 2, 3, 4, 5, 6
AC	alternating current (A)	n	coefficient of ideality
C_R	remaining battery capacity (A h)	n_p	number of parallel photovoltaic modules
C_p	Peukert capacity (A h)	P_{Bat}	battery power (W)
DC	direct current (A)	P_i	instantaneous power supplied to the load (W)
dod	depth of discharge	P_L	power of the load (W)
FMA	Fuzzy Management Algorithm	P_{PV}	photovoltaic power (W)
G	solar radiation (W/m ²)	PVP	photovoltaic panel
G_0	nominal solar radiation (W/m ²)	$PVPG$	photovoltaic power generation
I_{Bat}	battery current (A)	$P&O$	Perturb and Observe method for MPPT
I_i	instantaneous current supplied to the load (A)	q	electron energy (C)
I_{ph}	generated photo-current at a given irradiance G (A)	R_s	serial resistance of a photovoltaic module (Ω)
I_{pv}	current produced by the photovoltaic panel (A)	R_1, R_2, R_3	three switching relays
I_{PV}	current produced by the photovoltaic panel after the Maximum Power Point Tracking bloc (A)	T_a	ambient temperature at the panel surface ($^{\circ}\text{C}$)
I_r	reverse saturation current for a given ambient temperature (A)	T_{ref}	temperature of reference at the panel surface ($^{\circ}\text{C}$)
I_{r_Tref}	reverse saturation current for the temperature of reference (A)	V_c	open circuit voltage of a photovoltaic module (V)
I_{sc}	short circuit current for a given temperature T_a (A)	V_g	gap energy (eV)
I_{sc_Tref}	short circuit current for the temperature of reference (A)	$V_{t_T_a}$	thermal potential at the ambient temperature ($^{\circ}\text{C}$)
$MPPT$	Maximum Power Point Tracking		$x_{0i}, d_{0k}, y_{0j}, f_{0s}, e_{0n}$ and O_{0i} are, respectively, the values of the variables x, d, y, f, e and O in the membership intervals; and $\varepsilon_{x_{0i}}, \varepsilon_{d_{0k}}, \varepsilon_{y_{0j}}, \varepsilon_{f_{0s}}, \varepsilon_{e_{0n}}$ and $\varepsilon_{O_{0i}}$ are the range values of $x_{0i}, d_{0k}, y_{0j}, f_{0s}, e_{0n}$ and O_{0i} , respectively.
K	Boltzmann constant		
k_p	Peukert constant		

battery, a good use of the generated power and a stable supply for the load.

The following section describes the system components models. The Fuzzy Management Algorithm is detailed in Section 3, where the management strategy and the algorithm's execution are explained in depth. Some results are presented and discussed in Section 4. Finally, Section 5 gives a conclusion.

2. System modeling

The system under study is composed of a set of photovoltaic panels (with MPPT controllers), connected through relays to a Lead-acid battery bank (which includes the batteries and their regulators), and a variable load, using a DC bus, as presented in Fig. 1.

2.1. The PVP generation model

A non-linear model is used to model the photovoltaic panel. It is based on the daily measured radiation G and the ambient temperature T_a at the panel surface, which are used as inputs to a PVP generation model to evaluate the photovoltaic current I_{pv} . Thus, it is given by these equations [14]:

$$I_{pv} = n_p \left(I_{ph} - I_r \left(\exp \left(\frac{V_c + I_{pv} R_s}{V_{t_T_a}} \right) - 1 \right) \right) \quad (1)$$

$$I_{ph} = \frac{G}{G_0} I_{sc} \quad (2)$$

$$I_{sc} = I_{sc_Tref} (1 + (a(T_a - T_{ref}))) \quad (3)$$

$$I_r = I_{r_Tref} \left(\frac{T_a}{T_{ref}} \right)^{\frac{3}{n}} e^{\left(\frac{-qV_g}{nK} \left(\frac{1}{T_a} - \frac{1}{T_{ref}} \right) \right)} \quad (4)$$

$$I_{r_Tref} = \frac{I_{sc_Tref}}{e^{\frac{qV_c}{nKT_{ref}}}} - 1 \quad (5)$$

where I_{pv} is the estimated photovoltaic current (A), I_{ph} is the generated photo-current at a given irradiance G (A), I_{sc} is the short circuit current for a given temperature T_a (A), I_r is the reverse saturation current for a given temperature T_a (A), I_{r_Tref} is the reverse saturation current for the reference temperature T_{ref} (A).

The efficiency of the photovoltaic generation is ensured via the use of the MPPT bloc, where we adopted the P&O method for the extraction of the maximum electric power [8]. Hence, we obtain I_{PV} , the optimum photovoltaic current.

2.2. The battery model

For the Lead-acid battery, we adopt the nonlinear model given by [7]. Fig. 2 describes the equivalent circuit used for the lead acid battery, where I_{Bat} is positive when charging and negative when discharging and V_{Bat} is the battery output voltage. The charge of the battery (at instant k) is given by:

$$C_{R(k)} = C_{R(k-1)} + \frac{\partial t}{3600} k_p I_{Bat(k)} \quad (6)$$

where ∂t is the time between instant $k-1$ and k , and k_p is Peukert constant.

Thus, the depth of discharge dod is given by the following equation ($dod = 0$ when the battery is fully charged and $dod = 1$ when the battery is empty):

$$dod_{(k)} = \frac{C_{R(k)}}{C_p} \quad (7)$$

where C_R is the charged capacity and C_p is the capacity of Peukert, considered constant.

2.3. The load

To take into account the use of the expected electricity, we used a profile based on the consumption patterns of a typical family in Tunisia. Fig. 3 shows an hourly pattern for a typical day.

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات