



# Design and optimization of solid thermal energy storage modules for solar thermal power plant applications



Yongfang Jian<sup>a</sup>, Quentin Falcoz<sup>b,c</sup>, Pierre Neveu<sup>b,c</sup>, Fengwu Bai<sup>a</sup>, Yan Wang<sup>a</sup>, Zhifeng Wang<sup>a,\*</sup>

<sup>a</sup>Key Laboratory of Solar Thermal Energy and Photovoltaic System, Institute of Electrical Engineering, Chinese Academy of Sciences, Beijing 100190, China

<sup>b</sup>Laboratoire Procédés Matériaux et Energie Solaire (CNRS-PROMES), Font-Romeu 66120, France

<sup>c</sup>Université de Perpignan Via Domitia, Perpignan 66000, France

## HIGHLIGHTS

- An initial model is developed for a solid cylindrical heat storage unit.
- The analytical solution of the model is determined by using Laplace transform method.
- A new optimization method for the solid storage module design is proposed.
- The influence of design parameters on the storage cost is investigated.
- The optimization designs for various kinds of system requirement are studied.

## ARTICLE INFO

### Article history:

Received 15 May 2014

Received in revised form 8 October 2014

Accepted 10 November 2014

Available online 29 November 2014

### Keywords:

Optimization

Solid media sensible heat storage

Analytical solution

Solar thermal power

Modified lumped capacitance method

## ABSTRACT

Solid sensible heat storage is an attractive option for high-temperature storage applications in terms of investment and maintenance costs. Typical solid thermal energy storage systems use a heat transfer fluid to exchange heat as the fluid flows through a tubular heat exchanger embedded in the solid storage material. The modified lumped capacitance method is used with an effective heat transfer coefficient in a simplified analysis of the heat transfer in solid thermal energy storage systems for a solid cylindrical heat storage unit. The analytical solution was found using the Laplace transform method. The solution was then used to develop an optimization method for designing solid storage modules which uses the system requirements (released energy and fluid outlet temperature) as the constraint conditions and the storage module cost as the objective function for the optimization. Optimized results are then given for many kinds of system configurations.

© 2014 Elsevier Ltd. All rights reserved.

## 1. Introduction

Power generation using concentrated solar thermal energy is one of several promising renewable energy technologies with a great amount of worldwide research devoted to the development of concentrated solar energy systems in the last ten years [1,2]. Thermal energy storage (TES) is essential for concentrating solar power (CSP) plant applications. The main advantages of integrating a CSP system with thermal storage include extended utilization of the power block and life expectancy of components due to the reduction of thermal transients [3–5]. Therefore, TES systems give CSP plants an edge over photovoltaics or wind power [6].

There are three kinds of TES including sensible heat storage (SHS), latent heat storage (LHS) and thermo-chemical heat storage

(TCHS) that uses reversible endothermic chemical reactions. LHS is based on the change of state of a material. The thermal energy is stored when the material changes state as the heat of fusion or heat of vaporization. Presently, the development of phase change material and design of the LHS systems have been widely investigated [7–11]. SHS uses solid or liquid media and involves storing energy in a material without phase change in the temperature range of the storage process. This technology is the most mature and has been widely used in CSP systems. Currently, the two-tank molten salt storage system with a high-temperature tank and a low-temperature tank for storing the molten salt is the most mature utility-scale TES system for CSP plants. Such systems have been applied in parabolic trough power plants including Andasol (1–3) in Spain, Archimede in Italy [12,13] and the power tower plant Gemasolar in Spain [14]. However, the disadvantages of this design are the very high cost of the material used as heat transfer fluid (HTF) and storage material, the high cost of the heat

\* Corresponding author. Tel.: +86 10 82547035; fax: +86 10 62587946.

E-mail address: [zhifeng@vip.sina.com](mailto:zhifeng@vip.sina.com) (Z. Wang).



متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات