



A new combined cooling, heating and power system driven by solar energy

Jiangfeng Wang^a, Yiping Dai^{a,*}, Lin Gao^a, Shaolin Ma^b

^a Institute of Turbomachinery, School of Energy and Power Engineering, Xi'an Jiaotong University, No. 28 Xianning West Road, Xi'an, Shaanxi 710049, People's Republic of China

^b Dongfang Steam Turbine Works, Deyang 618201, People's Republic of China

ARTICLE INFO

Article history:

Received 3 September 2008

Accepted 6 June 2009

Available online 7 July 2009

Keywords:

Cycle
Ejector
Exergy
Optimization
Performance
Solar energy

ABSTRACT

A new combined cooling, heating and power (CCHP) system is proposed. This system is driven by solar energy, which is different from the current CCHP systems with gas turbine or engine as prime movers. This system combines a Rankine cycle and an ejector refrigeration cycle, which could produce cooling output, heating output and power output simultaneously. The effects of hour angle and the slope angle of the aperture plane for the solar collectors on the system performance are examined. Parametric optimization is conducted by means of genetic algorithm (GA) to find the maximum exergy efficiency. It is shown that the optimal slope angle of the aperture plane for the solar collectors is 60° at 10 a.m. on June 12, and the CCHP system can reach its optimal performance with the slope angle of 45° for the aperture plane at midday. It is also shown that the system can reach the maximum exergy efficiency of 60.33% under the conditions of the optimal slope angle and hour angle.

© 2009 Elsevier Ltd. All rights reserved.

1. Introduction

The trigeneration concept refers to the possibility of efficiently and profitably combining cooling, heating and power production (CCHP) to satisfy the consumption needs during the energy system operation. In a competitive energy market framework, the adoption of CCHP systems may become profitable with respect to traditional systems, where electricity, heat, and cooling are produced or purchased separately.

There are several current CCHP technologies to perform the trigeneration according to the prime movers, such as steam turbine, reciprocating internal combustion engine, gas turbine, micro gas turbine, stirling engine, fuel cell. Wang et al. [1] had made an extensive and an intensive review of CCHP in the literature. Wang et al. [2,3] also investigated the CCHP system driven by stirling engine and gas turbine. Li et al. [4] conducted the energy utilization evaluation for the CCHP systems mainly with gas engine and gas turbine as prime movers.

Although steam turbine, reciprocating internal combustion engine and gas turbine that can be considered as the conventional prime movers still make up most of the gross capacity being installed, and micro gas turbine, Stirling engine and fuel cell present a promising future for prime movers in CCHP system, the current CCHP

technologies must inevitably consume the fossil fuels, which would disappear with energy consumption and economic development in the future. So, it is necessary to utilize renewable energy.

The main objective of the present study is to propose a new combined cooling, heating and power (CCHP) system driven by solar energy. This system combines Rankine cycle and ejector refrigeration cycle, and produces cooling output, heating output and power output simultaneously. The ejector refrigeration cycle, which many studies [5–11] have been devoted to, is different from the absorption refrigeration cycle in most of CCHP systems. It has some advantages such as fewer movable parts and low operating, installation and maintenance cost. In addition, the ejector refrigeration cycle has the possibility of using a wide range of refrigerants with the system.

In the present study, the simulation of the CCHP system driven by solar energy is achieved using a simulation program. The effects of hour angle and the slope angle of the aperture plane for the solar collectors on the system performance are examined. In addition, the parameter optimization is achieved with exergy efficiency as the objective function by means of genetic algorithm under the given condition.

2. System description

The proposed CCHP system is driven by solar energy, and combines the Rankine cycle and the ejector refrigeration cycle, which could produce cooling, heating and power simultaneously. Fig. 1 illustrates the CCHP system. The overall system is divided into

* Corresponding author. Tel./fax: +86 029 82668704.
E-mail address: freego810211@gmail.com (Y. Dai).

Nomenclature		Subscripts	
A	surface area of solar collectors, m^2	a	acceptance half angle
b	width of absorber, m	b	beam
c	heat capacity, $kJ\ kg^{-1}$	br	branching
C	concentration ratio	B	boiler
D	diameter, m	C	condenser
E	exergy, kW	d	diffuse radiation; diffuser section of ejector
h	enthalpy, $kJ\ kg^{-1}$	e	effective
H	height, m	exg	exergy
I	hourly radiation, $W\ m^{-2}$	extr	extraction
k	heat transferring coefficient, $W\ m^{-2}\ K^{-1}$	E	evaporator
L	length of tube, m	fi	inlet of solar collectors
m	mass flow rate, $kg\ s^{-1}$	fo	outlet of solar collectors
ma	average number of reflections	g	global
n	the day of the year	hc	average temperature of heater
N	number of tubes	H	heater
p	pressure, MPa	i	Inlet
Q	heat load, kW	inst	Instantaneous
R	tilt factor; ratio	l	uniform
s	entropy, $kJ\ kg^{-1}\ K^{-1}$	lo	Loss
S	total effective flux, $W\ m^{-2}$	m	mixing section of ejector
t	temperature, $^{\circ}C$; time	mf	mixed fluid
T	temperature, K	n	nozzle
u	velocity, $m\ s^{-1}$	n1	inlet of nozzle
U	overall loss coefficient, $W\ m^{-2}\ K^{-1}$	n2	outlet of nozzle
W	width, m	NET	Net
Greek letters		p	pressure
α	absorptivity of the absorber surface	pf	primary flow
β	slope angle of the aperture plane for solar collectors, $^{\circ}$	P1	pump 1
δ	declination	P2	pump 2
η	efficiency	s	isentropic process
θ	angle of incidence	sc	average temperature of solar collectors
μ	entrainment ratio	sf	secondary flow
ρ	reflectivity of the concentrator surface; density, $kg\ m^{-3}$	thm	thermal
τ	transmissivity of the cover	T	turbine
ω	hour angle, $^{\circ}$	u	useful
φ	latitude, $^{\circ}$	z	zenith angle
		0	environment

two subsystems: the solar collector subsystem and the CCHP subsystem.

2.1. The solar collector subsystem

This subsystem consists of solar collectors, a thermal storage tank and an auxiliary heater. The solar collectors are used as a main energy source to supply heat to the system. The thermal storage tank is used as the thermal *source* when solar radiation is not sufficient. The auxiliary heater is installed as the backup energy source to boost the temperature of thermal storage tank to the allowable reference temperature when the temperature of thermal storage tank drops below the allowable reference temperature.

A compound parabolic collector (CPC) is used to collect the solar radiation because it achieves higher concentration for large acceptance angle and requires only intermittent sun-tracking. In addition, the CPC can achieve the higher temperature than flat plate collector for power generation. In the present study, the symmetric CPC with flat absorber is placed on a horizontal east–west axis and oriented with its aperture plane sloping at an angle of 45° .

The hourly global radiation I_g reaching a horizontal surface on the earth is given by:

$$I_g = I_b + I_d \quad (1)$$

where

$$I_b = I_{bn} \cos \theta_z \quad (2)$$

where I_{bn} is beam radiation in the direction of the rays, and θ_z is angle of incidence on a horizontal surface, i.e. the zenith angle.

It is postulated that for a clear cloudless day:

$$I_{bn} = A \exp \left[-\frac{B}{\cos \theta_z} \right] \quad (3)$$

and

$$I_d = C I_{bn} \quad (4)$$

where A , B and C are constants [12].

Since CPC for absorbing radiation is tilted at an angle to the horizontal, it is necessary to calculate the tilt factor for radiation.

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات