



# Robust optimization in relation to a basic safety investment model with imprecise probabilities

Terje Aven<sup>a,\*</sup>, Yolande Hiriart<sup>b</sup>

<sup>a</sup> University of Stavanger, Stavanger, Norway

<sup>b</sup> University of Franche-Comté (CRESE), Besançon, France

## ARTICLE INFO

### Article history:

Received 13 August 2012

Received in revised form 20 December 2012

Accepted 2 January 2013

Available online 15 February 2013

### Keywords:

Robust optimization  
Imprecise probabilities  
Safety investment model  
Sensitivity analyses

## ABSTRACT

Consider the following basic model in economic safety analysis: a firm is willing to invest an amount  $x$  in safety measures to avoid an accident  $A$  which, in the case of occurrence, leads to a loss of size  $L$ . The probability of an accident is a function of  $x$ . The optimal value of  $x$  is determined by minimizing the expected costs. In the present paper we study this model (and an extended version of it) in an applied risk/safety management setting, which allows for imprecise probabilities for the accident probabilities. The imprecision reflects the fact that the knowledge basis for assigning the probabilities is poor and based on many assumptions, and also that there are different knowledge bases among relevant experts and stakeholders. The purpose of the paper is to present and discuss a set-up for the precise formulation of this type of problems and show how they can be solved. We demonstrate in the paper how an optimal investment level  $x$  can be determined under different sets of situations and conditions, including one where a tolerability limit is defined for the accident probability. The main conclusion of the paper is that the robust optimization methods could in practice provide useful decision support but should be supplemented with sensitivity analyses showing the optimal investment levels for various parameter values followed by qualitative analyses providing arguments supporting the different parameter values.

© 2013 Elsevier Ltd. All rights reserved.

## 1. Introduction

We consider the basic safety investment model first proposed by Shavell (1984) and followed by Schmitz (2000) and Hiriart et al. (2004) among others, which provides guidance for the decision making and can be described as follows:

A firm is willing to invest an amount  $x$  in safety measures to avoid an accident  $A$  which, in the case of occurrence, leads to a loss of size  $L$ . The probability of an accident is a function of  $x$ . The optimal value of  $x$  is determined by minimizing the total expected costs.<sup>1</sup>

This model allows for the determination of the proper level of investment in prevention from the firm's perspective. In Aven and Hiriart (2011), this model and extended versions of it, are re-examined by adopting a practical risk/safety management perspective. The authors question how the model can be used for guiding the firm and regulators in determining the proper level of investment in safety. Attention is given to issues like how to specify the accident

probability and how to take into account uncertainties that extend beyond the expected value. It is concluded that the model, with suitable extensions and if properly implemented, provides a valuable decision support tool: the focus on investment levels stimulates the generation of alternative risk-reducing measures, and the model is thus particularly useful in risk reduction (ALARP) processes.<sup>2</sup>

In all these applications of the model, it is assumed that the probability of an accident is specified by one number. It is a subjective (also referred to as a judgmental or knowledge based) probability.<sup>3</sup> An assigned probability  $P$  expresses the analyst's judgment of the event under consideration (say  $A$ ) given his/her background knowledge (here called  $K$ ); i.e., we can write  $P = P(A|K)$ . Different interpretations can be given for this probability but in line with Lindley (2006), the uncertainty standard meaning is used in this paper:

The probability is a subjective probability. For instance, if we assign a probability of 0.1 to the event  $A$ , we compare our uncertainty (i.e. our degree of belief) of  $A$  occurring with a standard event like drawing a red ball from an urn containing 10 balls of which one is red.

\* Corresponding author. Tel.: +47 51831000/2267; fax: +47 51831750.

E-mail address: [terje.aven@uis.no](mailto:terje.aven@uis.no) (T. Aven).

<sup>1</sup> The common goal of the cited papers (Shavell, 1984; Schmitz, 2000; Hiriart et al., 2004) is ultimately to define the optimal public intervention regarding agents creating risks for others in the economy. The behaviour of these risky agents with respect to safety investments is modelled as described here.

<sup>2</sup> ALARP: As Low As Reasonably Practicable.

<sup>3</sup> Note that in Bayesian analysis it is common to introduce probability models with parameters, and use subjective distributions to reflect the epistemic uncertainties about these parameters. In our set-up such a probability model is however not introduced.

However, in many situations the basis for assigning the probabilities could be weak, for example concerning the accident probability for a specific investment in our case. A specific number can of course always be assigned, but the rationale for it can be questioned – strong assumptions may be needed to justify a concrete number. The assigned probability is precise, but may be considered rather arbitrary. Other analysts could have produced very different numbers. This type of considerations has led to the use of interval probabilities or imprecise probabilities. This theory generalizes probabilities by using an interval  $[\underline{P}(A), \overline{P}(A)]$  to represent uncertainty (degree of belief) about an event  $A$ , with lower probability  $\underline{P}(A)$  and upper probability  $\overline{P}(A)$ , where  $0 \leq \underline{P}(A) \leq \overline{P}(A) \leq 1$ . The imprecision in the representation of the event  $A$  is defined by  $\Delta P(A) = \overline{P}(A) - \underline{P}(A)$ . In line with the uncertainty standard interpretation of a subjective probability, we interpret an imprecision interval, say  $[0.1, 0.5]$  for the probability  $P(A)$  in this way (Lindley, 2006, p. 36; Aven, 2011): the analyst states that his/her assigned degree of belief is greater than the urn chance of 0.10 (the degree of belief of drawing one particular ball out of an urn comprising 10 balls) and less than the urn chance of 0.5. The analyst is not willing to make any further judgments.

The use of the imprecision interval is a debated topic in the applied probability literature (see Aven, 2011, for example). This discussion is, however, outside the scope of the present paper. Here we simply assume that an imprecise probability set-up is considered appropriate for reflecting the aspects mentioned above concerning the problems of supporting a specific probability number when the background knowledge is weak. In the paper we re-examine the basic safety investment model and some related extended versions of this model, when allowing for imprecise probabilities. The search for an optimal investment  $x$  then becomes a robust optimization problem, and we can apply theory and methods from this area to solve it. This we will do in Section 3 after a brief presentation of the basic investment model with extensions. Section 4 discusses the results as well as the total set-up and approach taken to deal with this type of problem, and the final Section 5 provides some conclusions. The robust optimization field is rather technical, and, to avoid too many details, the examples introduced in Section 3 are rather simple. However, for the purpose of the present paper – which highlights the main ideas – the examples are considered sufficiently informative. Through the examples we are able to conclude on the suitability of the robust optimization methods, and compare this approach with others, in particular one using a sensitivity analysis showing the optimal investment levels for various parameter values, followed by qualitative analyses providing arguments supporting the different parameter values. Extending the models beyond the model set-up defined in Section 3 would not have given us notable new insights on these issues, nor allowed us to present all analytical steps of the analysis. It is a main goal of the present paper to show the safety community what the robust optimization theory and methods can in fact do. It is thus essential that the reader is able to follow each step of the methods. From the set-up and the examples, the analysts get a foundation for the proper formulation of their problems, and a basis for selecting a suitable analysis approach. These issues are highlighted in this paper, not the technicalities linked to various extensions of the basic model. The examples we are using are detailed enough to demonstrate the points we would like to make concerning the suitability of the robust optimization methods in the case studied.

## 2. The basic investment model with extensions

In this section we summarise the key features of the basic safety investment model, with some extensions and clarifications.

Let  $I(B)$  be the indicator function which is equal to 1 if the argument is true and 0 otherwise; i.e., it is 1 if the event  $B$  occurs and zero otherwise. The model expresses that the costs  $C$  for the time period considered can be written

$$C = x + I(A)L,$$

where as above  $x$  is the investment level,  $A$  is the accident event and  $L$  is the loss given the occurrence of  $A$ . The model is easily extended to the accident events  $A_1, A_2, \dots, A_n$  by the formula

$$C = x + \sum_i I(A_i)L_i, \quad (2.1)$$

where  $L_i$  is the loss in the case that the accident event  $A_i$  occurs. For an oil and gas production unit offshore typical such events are gas leakages, well kicks (loss of well control), vessel on collision course, and structural damage. For some of these events, a set of sub-events is defined, for example leakages of different sizes.

Let  $p_i(x)$  denote the probability of the accident event  $A_i$  given the investment  $x$ . The probability  $p(x)$  is a subjective probability understood as explained in the previous section.

It follows from formula (2.1) that the expected cost  $f(x)$  defined by  $f(x) = E[C|x]$  can be written as:

$$f(x) = x + \sum_i p_i(x)E[L_i], \quad (2.2)$$

where  $E[L_i]$  refers to the expected loss (with respect to the subjective probability distribution of  $L_i$ ) given the occurrence of the accident event  $A_i$ . Assuming that the probability  $p_i(x)$  is differentiable with a derivative  $p'_i(x) < 0$ , the optimal investment level  $x$  must satisfy:

$$1 = -\sum_i p'_i(x)E[L_i].$$

This equality is the usual equalization between marginal costs and marginal benefits associated with the investment in prevention. This condition can be interpreted as follows: starting from zero, prevention is increased up to the point where the cost of an additional unit (here the first term equal to 1) is just equal to the expected losses avoided (here  $-\sum_i p'_i(x)E[L_i]$ ), obtained through a reduction in the probability of occurrence).

To adjust the model to include the case where the investment also allows for reductions of the expected losses, let  $E[L_i|x]$  denote the expected loss given an investment  $x$ . The optimization function then becomes

$$f(x) = x + \sum_i p_i(x)E[L_i|x], \quad (2.3)$$

and, assuming that  $E[L_i|x]$  is also a smooth function of  $x$ , the optimal level of investment  $x$  can be determined as above. It is then characterized by the condition  $1 = -\sum_i p'_i(x)E[L_i|x] - \sum p_i(x)(E[L_i|x])'$ , where the new term takes into account the fact that safety measures can also influence the expected size of losses.

This model can be extended by allowing for different investments for the various accident events. More money could, for example, be used on leakages compared to ship collisions. In this case, the total expected cost  $f$  becomes a function of the vector of event investment  $1, 2, \dots, n$ . To avoid too many technicalities, we focus on the one-variable case of  $f(x)$ , where  $f$  is defined by  $x + p(x)E[L]$  or  $x + \sum_i p_i(x)E[L_i|x]$ .

The assigned probabilities and the expected values depend on the assessor. As a basis for the assignment of  $p(x)$ , the analysts need to perform a risk analysis, and for a given investment level we seek the risk-reducing measure that gives the lowest accident probability. Similarly, using risk assessment, the expected loss given that an accident event has occurred,  $E[L|x]$ , is determined. The situation could be quite complex when the losses relate not only to

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات