

3rd International Conference on Recent Trends in Computing 2015 (ICRTC-2015)

IPv6 address auto-configuration protocol for mobile Ad Hoc Networks

K. Sahadevaiah^{1*}, N. Ramakrishnaiah², Prasad Reddy P.V.G.D.³

^{1,2}Department of Computer Science & Engineering, University College of Engineering,
Jawaharlal Nehru Technological University, KAKINADA-533003, AP (India)

³Department of Computer Science and Systems Engineering, AU College of Engineering,
Andhra University, VISAKHAPATNAM-5300003, AP (India)

Abstract

The major task of an address autoconfiguration protocol in Mobile Ad hoc Networks (MANETs) is to manage the resource address space efficiently and effectively. An unconfigured node should be able to allocate a unique network address in a timely manner. Once a node leaves the network, its address should be reclaimed for future usage. The lack of a central server and hosts' mobility makes address allocation a challenging task in ad hoc networks. In recent years, various address autoconfiguration protocols have been proposed in the literature. In this paper, we present an IPv6 address configuration scheme that can allocate IPv6 addresses to the authorized hosts for a MANET. Each host can generate unique IPv6 address from its own IPv6 address and can assign those addresses to the new nodes. The scheme has been implemented in network simulator 3.13 with Ubuntu. Simulation outcome has shown that the scheme is robust and IP addresses can be allocated to nodes with an acceptable addressing latency and communication overhead.

Keywords: Mobile Ad Hoc Network, IP Address Assignment, IPv6, Dynamic Address, Autoconfiguration, Duplicate address detection

1. Introduction

Mobile Ad hoc network (MANET) is an independent self-configuring wireless communication infrastructure-less network of mobile nodes connected by wireless links. The major challenges in MANETs are: automatic IP address configuration, scalable routing and security. The autoconfiguration protocols are classified into three categories: stateful approaches, stateless approaches and hybrid approaches [1]. A *stateful approach* assumes the existence of a central entity to keep an address allocation table for whole network and assigns unique IP address for unconfigured node. i.e. the nodes know the network state. *Stateless approaches* do not need a central entity to maintain an address allocation table. Instead, each node selects an address by itself randomly and verifies its uniqueness with the so-called *duplicate address detection* (DAD) procedure. If duplication is detected, at least one of the nodes with duplicate addresses must change its address. *Hybrid approaches* combine both stateful and

* Corresponding author. Tel.: +91 950 266 1429
E-mail address: ksd1868@gmail.com

stateless mechanisms to improve the scalability and reliability of the autoconfiguration, but may result in higher complexity and higher protocol overhead.

A node cannot take part in a communication, unless it has its own IP address. For an automatic IP address assignment in wired networks, nodes may use a dynamic host configuration protocol (DHCP) to acquire an IP address from a centralized server. However, this solution cannot be used in MANETs due to the mobility of nodes and difficulty of maintaining a centralized DHCP server. Many dynamic address configuration protocols have been proposed for MANET. However, most of the protocols rely on passive duplicate address detection (DAD) mechanism to resolve the address conflicts lack a mechanism for authentication.

In this paper, we present an IPv6 address configuration scheme that can allocate IPv6 addresses to the authorized hosts for a MANET. The proposed scheme does not require broadcasting entire MANET for duplicate address detection (DAD). Each host in the network can generate a node ID and a unique IPv6 address for a new authorized host. Thus, a node can be identified by the unique tuple (*node_id*, *IP address*) [2], which adds a node authentication feature in addition to identification.

The rest of the paper is organized as follows. Section 2 provides system model. Section 3 explains the proposed scheme. Section 4 describes the performance and simulation results. Finally, section 5 concludes the paper.

2. System Model

We consider the formation of an autonomous ad hoc network starting from one node and, then, the other nodes join the network one by one. The autonomous ad hoc network that is considered has no gateway or no external connection to any other network. The nodes are free to move around and can leave or join network at any time. Nodes are identified by unique tuple (*node_id*, *IPv6 address*). The IPv6 address configuration protocols can configure a node with a unique address. A new node first requests an address from a neighbor node. If the neighbor nodes do not have the address space, then the new node requests an address from a remote node. In the latter case, both the cost and the delay are increased. Every node, except root node, contains a counter variable *count* which specifies number of IP addresses can be allocated by a node. Value of counter variable can be in the range of 10-100.

The Figure 1 depicts how an address is allocated for first 10 nodes. Starting from the root node with an IP fe80:0000:0000:0000:0000:0000:0001. Here, network prefix fe80:0000:0000:0000 is omitted for remaining nodes, as network prefix remains unchanged throughout address allocating process. It may be noted that, allocating of IP address may not follow the same order as shown in below tree. It depends upon neighbours nodes. The below tree depicts the order of address allocation for 10 nodes in our simulation. Node numbers gives the order in which nodes entered into simulation. Hence, node 1 entered first and node 2 arrived after node 1 and so on.

3. Proposed Scheme

The proposed scheme dynamically allocates the IP addresses to the hosts in the network. When a new host wants to join an ad hoc network, it periodically issues a *DETECT* broadcast message along with its signature to its neighbours till it either receives a *PROVIDE* message or a *REFUSE* message. If no *PROVIDE* or *REFUSE* message is received, it means that there are no neighbour nodes, the new host configures itself as a root node to the IP address, say, fe80:0000:0000:0000:0000:0000:0001 and generates a unique network ID (NID) as a network identifier and also node identifier (*node_id*).

If new host receives the signed *PROVIDE* (provideIP) message from one or more neighbours, it chooses the smallest IP address that is offered to it. After choosing smallest IP address, a signed *CHOOSE* message is sent back to the proxy offering that IP address indicating that new host has chosen the IP provided by proxy. Proxy

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات