ELSEVIER

Contents lists available at ScienceDirect

Applied Energy

journal homepage: www.elsevier.com/locate/apenergy



Development and application of China provincial road transport energy demand and GHG emissions analysis model



Tianduo Peng^{a,b}, Xunmin Ou^{a,b,*}, Zhiyi Yuan^{a,b}, Xiaoyu Yan^{c,*}, Xiliang Zhang^{a,b}

- ^a Institute of Energy, Environment, Economy(3E), Tsinghua University, Beijing 100084, China
- ^b China Automotive Energy Research Center (CAERC), Tsinghua University, Beijing 100084, China
- ^c Environment and Sustainability Institute, University of Exeter, Penryn, Cornwall TR10 9FE, UK

HIGHLIGHTS

- A provincial model for road transport energy demand and GHG emissions in China.
- China's vehicle stock will keep increasing and reach 540 million in 2050.
- EV can have great impact on road transport energy demand and GHG emissions.
- Future vehicle ownership and GHG emissions vary among Chinese provinces.

ARTICLE INFO

Keywords: Transportation energy Vehicle stock Energy demand GHG emissions EV China

ABSTRACT

Energy consumption and greenhouse gas (GHG) emissions of China's road transport sector have been increasing rapidly in recent years. Previous studies on the future trends trend to focus on the national picture and cannot offer regional insights. We build a novel bottom-up model to estimate the future energy demand and GHG emissions of China's road transport at a provincial level, considering local economic development, population and policies. Detailed technical characteristics of the future vehicle fleets are analyzed in several up-to date scenarios. The results indicate that China's vehicle stock will keep increasing to 543 million by 2050. The total direct petroleum demand and associated GHG emissions will peak at 508 million tonnes of oil equivalent (Mtoe) and 1500 million tonnes CO₂ equivalent (Mt CO_{2.e}) around 2030 in the Reference scenario. Natural gas vehicle diffusion has a large impact on petroleum demand reduction in the short term, with decreases of 41-46 Mtoe in 2050. Compared to the Reference case, battery electric and fuel cell vehicles will reduce petroleum demand by 94-157 and 28-54 Mtoe in 2050, respectively. When combined with decarbonization of future power supply, battery electric vehicles can play a significant role in reducing Well-to-Wheels GHG emissions in 2050 with 295-449 Mt CO_{2.e} more reductions. The spatial distributions of future vehicle stock, energy demand and GHG emissions vary among provinces and show a generally downward trend from east to west. Policy recommendations are made in terms of the development of alternative fuels and vehicle technologies considering provincial differences, expansion of natural gas vehicle market and acceleration of electric vehicle market penetration.

1. Introduction

Road transport plays an important role in transport energy consumption and GHG emissions in the world. Globally, transport sector accounts for about one-fourth of the total fossil fuel CO₂ emissions with about three quarters of the transport sector CO₂ emissions incurred by road transport [1,2]. China has been the largest vehicle producer and

consumer from 2008 and its road transport represents about 85% or more of transport sector energy consumption and GHG emissions [3]. Vehicle stock in China has risen from 26.9 million in 2004 to 162.8 million in 2015 with an average annual growth rate of more than 17%, and vehicle sales have risen from 5.1 million in 2004 to 24.6 million in 2015 with an average annual growth rate of 16% [4,5]. With the rapid growth of vehicle stocks, the energy demand and GHG emissions

^{*} Corresponding authors at: Institute of Energy, Environment, Economy(3E), Tsinghua University, Beijing 100084, China (X. Ou); Environment and Sustainability Institute, University of Exeter, Penryn, Cornwall TR10 9FE, UK (X. Yan).

E-mail addresses: ptd15@mails.tsinghua.edu.cn (T. Peng), ouxm@mail.tsinghua.edu.cn (X. Ou), yuan-zy16@mails.tsinghua.edu.cn (Z. Yuan), Xiaoyu.Yan@exeter.ac.uk (X. Yan), zhang_xl@tsinghua.edu.cn (X. Zhang).

T. Peng et al. Applied Energy 222 (2018) 313–328

Nomenclature		CM	coal derived methanol
_	1 4 5 1 4 1000 4	CTL	coal-to-liquids
E	elasticity between vehicle growth and GDP growth	CNG	compressed natural gas
EN	direct energy demand of road transport	CPREG	China Provincial Road Transport Energy Demand and
EN_{WTW}	Well-to-Wheels energy demand of road transport		GHG Emissions Analysis
EM	direct greenhouse gas emissions of road transport	$CO_{2,e}$	CO ₂ equivalents
EM_{WTW}	Well-to-Wheels greenhouse gas emissions of road trans-	EV	electric vehicle
	port	FCR	fuel consumption rate
P	population	FCV	fuel cell vehicle
PGDP	per capita gross domestic product	GDP	gross domestic product
Sale	vehicle sale	GHG	greenhouse gas
S	survival ratio	HT	heavy duty truck
vs	vehicle ownership (in numbers of 1000 people)	ICE	internal combustion engine
VS	vehicle stock	ICEV	internal combustion engine vehicle
		LC	low carbon
Greek symbol		LNG	liquefied natural gas
		LT	logistics truck
α, β	curvature parameters related to Gompertz function	Mt	million tonnes
		MT	medium duty truck
Subscripts		NB	non-urban transit bus
		NG	natural gas
i	the studied province	NGV	natural gas vehicle
j	vehicle type	PV	non-taxi passenger vehicle
k	vehicle fuel type	REF	reference scenario
m	sold time of vehicle	SAE-China	Society of Automotive Engineering of China
t	calendar year	ST	sanitation truck
		toe	tonne of oil equivalent
Abbreviations		TV	taxi
		UB	urban transit bus
AF	alternative vehicle fuel	VMT	vehicle miles traveled
BAU	business as usual	WTW	Well-to-Wheels
BD	bio-diesel		
BE	bio-ethanol		

associated with on-road vehicles have become a major challenge in China. About 90% of gasoline and 60% of diesel are consumed by road vehicles according to Ou et al. [6] and the growth rates of GHG emissions from road transport in China consistently exceed the rates of economic growth [7]. With sustained economic development and urbanization, China will continue to suffer from great pressure from energy conservation and emission reduction in road transport. The vehicle stock is expected to increase to 500–600 million in 2050 [8–10] from 192 million in 2016 [4] and GHG emissions from China's road transport will accounts for 12% of the national total in 2030 [11].

The Chinese government is seeking more effective policies to curb energy demand and reduce GHG emissions from road transport. To provide relevant recommendations for policy makers, studies estimating the future trends of energy demand and GHG emissions in China's road transport are highly necessary. Due to differences in population and level of socio-economic development, future trends of road transport development will vary significantly between provinces. Several polices at the national level have been introduced by Chinese government to promote energy conservation and emission reduction in road transport sector, including improving vehicle energy efficiency, enhancing the penetration of new energy vehicles and promoting alternative fuel. However, it would be more efficient and effective to provide province-specific policies considering geographical and socio-economic differences.

Bottom-up analysis is a widely used approach to forecasting energy demand and GHG emissions from road transport, by which many important factors such as the growth of vehicle stock, vehicle technology development, vehicle mileage travelled, fuel efficiency improvement and even policy measures can be analyzed in detail. Based on different bottom-up model, several studies have assessed the energy

consumption and GHG emissions of road transport in different countries. Aggarwal et al. [12] analyzed the energy demand and $\rm CO_2$ emissions in the Delhi region for 2021 under various scenarios. Palencia et al. [13] estimated the vehicle market composition and calculated the energy consumption and $\rm CO_2$ emissions of Japan's passenger light-duty vehicle in the long term. Garcia et al. [14] projected the life-cycle GHG emissions of the Portuguese light-duty fleet by 2030 under four scenarios, especially focusing on the impact of battery electric vehicles.

Also, the energy demand and GHG emissions of China's road transport have been analyzed extensively in previous studies [3,6,10,11,15–20]. For example, He et al. [15] developed a bottom-up model to calculate the historical oil consumption and CO2 emissions of road transport in China and forecast the future trends of vehicle population using an elasticity method. Hao et al. [16] employed a bottomup model to project vehicle ownership and simulate energy consumption and GHG emission of the passenger vehicle fleet, and evaluated several key measures to realize fuel conservation and GHG emissions reduction through to 2050. Zhang et al. [17] evaluated the vehicles stocks using an elastic coefficient method and analyzed long-term fuel consumption of vehicles in China based on the LEAP modelling tool. Wu et al. [10] predicted the future vehicle stocks with Gompertz function and calculated vehicle energy demand through to 2050 in China. Ou et al. [6] used a bottom-up model based on future sales projection of all vehicle types to analyze the Well-to-Wheels (WTW) life-cycle energy demand and GHG emissions of China's future road transport. Using the same method, Gambhir et al. [11] calculated the CO2 emissions of China's on road vehicles and conducted analysis on ways to reduce CO2 emissions of China's road vehicles during the period of 2010-2050. Several studies conducted analysis of China's road transport using other methods. For instance, Chai et al. [18] studied the relevant factors

دريافت فورى ب متن كامل مقاله

ISIArticles مرجع مقالات تخصصی ایران

- ✔ امكان دانلود نسخه تمام متن مقالات انگليسي
 - ✓ امكان دانلود نسخه ترجمه شده مقالات
 - ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 - ✓ امكان دانلود رايگان ۲ صفحه اول هر مقاله
 - ✔ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 - ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات