

## Accepted Manuscript

Modelling intergranular and transgranular micro-cracking in polycrystalline materials

V. Gulizzi, C.H. Rycroft, I. Benedetti

PII: S0045-7825(17)30674-6  
DOI: <https://doi.org/10.1016/j.cma.2017.10.005>  
Reference: CMA 11632

To appear in: *Comput. Methods Appl. Mech. Engrg.*

Received date : 29 June 2017  
Revised date : 25 September 2017  
Accepted date : 3 October 2017

Please cite this article as: V. Gulizzi, C.H. Rycroft, I. Benedetti, Modelling intergranular and transgranular micro-cracking in polycrystalline materials, *Comput. Methods Appl. Mech. Engrg.* (2017), <https://doi.org/10.1016/j.cma.2017.10.005>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



# Modelling intergranular and transgranular micro-cracking in polycrystalline materials

V. Gulizzi<sup>a,b,1</sup>, C. H. Rycroft<sup>b,c</sup>, I. Benedetti<sup>a,\*</sup>

<sup>a</sup>*Dipartimento di Ingegneria Civile, Ambientale, Aerospaziale, dei Materiali - DICAM  
Università degli Studi di Palermo, Viale delle Scienze, 90128, Palermo, Italy*

<sup>b</sup>*Paulson School of Engineering and Applied Sciences,  
Harvard University, Cambridge, MA 02138, USA*

<sup>c</sup>*Mathematics Group, Lawrence Berkeley National Laboratory, Berkeley, CA 94720, USA*

---

## Abstract

In this work, a grain boundary formulation for intergranular and transgranular micro-cracking in three-dimensional polycrystalline aggregates is presented. The formulation is based on the displacement and stress boundary integral equations of solid mechanics and it has the advantage of expressing the polycrystalline problem in terms of grain boundary variables only. The individual grains within the polycrystalline morphology are modelled as generally anisotropic linear elastic domains with random spatial orientation. Transgranular micro-cracking is assumed to occur along specific cleavage planes, whose orientation in space within the grains depend upon the crystallographic lattice. Both intergranular and transgranular micro-cracking are modelled using suitably defined cohesive laws, whose parameters characterise the behaviour of the two mechanisms. The algorithm developed to track the inter/transgranular micro-cracking history is presented and discussed. Several numerical tests involving pseudo-3D and fully 3D morphologies are performed and analysed. The presented numerical results show that the developed formulation is capable of tracking the initiation and evolution of both intergranular and transgranular cracking as well as their competition, thus providing a useful tool for the study of damage micro-mechanics.

*Keywords:* Polycrystalline materials; Transgranular cracking; Intergranular cracking; Micro-mechanics; Cohesive zone modelling; Boundary element method.

---

---

\*Corresponding author

*Email addresses:* [vincenzo.gulizzi@unipa.it](mailto:vincenzo.gulizzi@unipa.it) (V. Gulizzi), [chr@seas.harvard.edu](mailto:chr@seas.harvard.edu) (C. H. Rycroft), [ivano.benedetti@unipa.it](mailto:ivano.benedetti@unipa.it) (I. Benedetti)

<sup>1</sup>On a research leave from the University of Palermo, Italy.

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات