## Accepted Manuscript

Investigating the Soil Removal Characteristics of Flexible Tube Coring Method for Lunar Exploration

Junyue Tang, Qiquan Quan, Shengyuan Jiang, Jieneng Liang, Xiangyong Lu, Fengpei Yuan

PII:	\$0273-1177(17)30781-0
DOI:	https://doi.org/10.1016/j.asr.2017.10.043
Reference:	JASR 13475
To appear in:	Advances in Space Research
Received Date:	28 June 2017
Revised Date:	17 October 2017
Accepted Date:	23 October 2017



Please cite this article as: Tang, J., Quan, Q., Jiang, S., Liang, J., Lu, X., Yuan, F., Investigating the Soil Removal Characteristics of Flexible Tube Coring Method for Lunar Exploration, *Advances in Space Research* (2017), doi: https://doi.org/10.1016/j.asr.2017.10.043

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

## Investigating the Soil Removal Characteristics of Flexible Tube Coring Method for Lunar Exploration

Junyue Tang<sup>a</sup>, Qiquan Quan<sup>a</sup>, Shengyuan Jiang<sup>a,\*</sup>, Jieneng Liang<sup>a</sup>, Xiangyong Lu<sup>b</sup>, Fengpei Yuan<sup>c</sup>

<sup>a</sup>State Key Laboratory of Robotics and System, Harbin Institute of Technology, No.92, Xidazhi St., Nangang Dist., Harbin, 150001, P.R. China.

<sup>b</sup>School of Mechatronic Engineering, China University of Mining and Technology, No.1, College Rd., Quanshan Dist., Xuzhou, 221116, P.R. China.

<sup>c</sup>Department of Mechanical, Aerospace and Biomedical Engineering, The University of Tennessee, Knoxville, 124 Perkins Hall, Knoxville, TN, 37996, USA.

## Abstract

Compared with other technical solutions, sampling the planetary soil and returning it back to Earth may be the most direct method to seek the evidence of extraterrestrial life. To keep sample's stratification for further analyzing. a novel sampling method called flexible tube coring has been adopted for China future lunar explorations. Given the uncertain physical properties of lunar regolith, proper drilling parameters should be adjusted immediately in piercing process. Otherwise, only a small amount of core could be sampled and overload drilling faults could occur correspondingly. Due to the fact that the removed soil is inevitably connected with the cored soil, soil removal characteristics may have a great influence on both drilling loads and coring results. To comprehend the soil removal characteristics, a non-contact measurement was proposed and verified to acquire the coring and removal results accurately. Herein, further more experiments in one homogenous lunar regolith simulant were conducted, revealing that there exists a sudden core failure during the sampling process and the final coring results are determined by the penetration per revolution index. Due to the core failure, both drilling loads and soil's removal states are also affected thereby.

Keywords: Lunar exploration; Flexible tube coring; Soil removal

\*Corresponding authors Email address: jiangshy@hit.edu.cn (Shengyuan Jiang)

Preprint submitted to Advances in Space Research

October 30, 2017

## دريافت فورى 🛶 متن كامل مقاله

- امکان دانلود نسخه تمام متن مقالات انگلیسی
  امکان دانلود نسخه ترجمه شده مقالات
  پذیرش سفارش ترجمه تخصصی
  امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
  امکان دانلود رایگان ۲ صفحه اول هر مقاله
  امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
  دانلود فوری مقاله پس از پرداخت آنلاین
  پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات
- ISIArticles مرجع مقالات تخصصی ایران