#### Energy 126 (2017) 733-745

Contents lists available at ScienceDirect

### Energy

journal homepage: www.elsevier.com/locate/energy

## The choice of energy saving modes for an energy-intensive manufacturer under non-coordination and coordination scenarios

Jianjun Ouyang <sup>a, \*</sup>, Peng Ju <sup>b</sup>

<sup>a</sup> School of Economics and Management, Shihezi University, Shihezi 832003, PR China
<sup>b</sup> School of Engineering and Management, Nanjing University, Nanjing 210093, PR China

#### ARTICLE INFO

Article history: Received 29 July 2016 Received in revised form 20 February 2017 Accepted 14 March 2017

Keywords: Energy saving management Energy performance contracting Supply chain coordination Revenue-sharing Game model

#### ABSTRACT

Energy-intensive manufacturers have two main options for improving their energy efficiency: design and implement energy efficiency projects on their own (we call this self saving), or enter into energy performance contracts (EPCs), which mainly include shared savings and guaranteed savings. In this paper, we will discuss an energy-intensive manufacturer facing self saving and shared savings options and how this manufacturer chooses the optimal energy saving mode under non-coordination and coordination scenarios. We first formulate several mathematical models of the two types of energy-saving modes based on the assumption of exogenous unit savings (EX). We show that when the unit energy-saving benefit from shared savings is greater than the unit energy-saving benefit from self saving, the manufacturer prefers shared savings under the non-coordination scenario; otherwise, the manufacturer prefers self saving. Furthermore, we find that the bargaining power of the manufacturer is also a key factor in addition to the difference of unit energy-saving benefits under the coordination scenario. Interestingly, sometimes the bargaining power of the manufacturer has no impact on the optimal choices of energy saving modes are completely different from the basic model. © 2017 Elsevier Ltd. All rights reserved.

#### 1. Introduction

Energy-intensive manufacturers (hereafter referred to as manufacturers) face three "big mountains." The first is the relatively rapid rise in energy prices. The second is increasingly stringent environmental policies. For example, the U.S.- China Joint Announcement on Climate Change (JACC) states that China intends to achieve its peak CO<sub>2</sub> emissions in approximately 2030. Finally, the consumer awareness of environmental protection is growing. For example, suppliers of Tesco, Walmart, IBM, and IKEA have been required to provide carbon labels [1]. These can greatly erode the profits of these manufacturers. Thus, improving energy efficiency becomes one of the most effective means by which manufacturers can address those pressures. Kim and Worrell [2] benchmarked the energy efficiency of steel production to best practice performance in five countries with over 50% of world steel production, finding that potential carbon emissions reduction due to energy efficiency improvement varies from 15% (Japan) to 40% (China, India, and the

\* Corresponding author. E-mail address: 381100ouyang@sina.com (J. Ouyang). U.S.). As another example, in the cement industry, benchmarking and other studies have demonstrated the technical potential for up to 40% improvement in energy efficiency [3].

In practice, manufacturers can design, construct, and operate energy efficiency projects on their own to improve energy efficiency. This approach has some common characteristics: manufacturers depend mainly on their own strength, they provide project financing themselves, and they bear all the risk of the projects but retain all the savings. For the sake of brevity, we will call this self saving. In 2005, Pfizer Fribourg, as one of the world's largest biopharmaceutical companies, began to improve energy efficiency by self saving [4]. Large-scale manufacturers often have the potential to proceed with self saving energy efficiency projects. Such companies usually include a separate department dedicated to safety and environmental issues and hire specialists in this field. However, there are many disadvantages when some manufacturers choose self saving, such as lack of knowledge and experience during the design phase, uninformed use of energy efficiency equipment during the operational phase, etc. All the above factors may lead to a failure of project savings not making up for investment costs, which results in many potential energy efficiency projects not





<b>Nomenclature</b> $\Pi_{ESCO}^{EXC}$ Profit of the ESCO under EXC scenario			
			Profit of the manufacturer under EN scenario
EX	Exogenous unit savings	$\prod_{m,b}^{EN}$	
EN	Endogenization of unit savings	$\prod_{m,s}^{ENN}$	Profit of the manufacturer under ENN scenario
EXN	Exogenous unit savings and non-coordination	$\prod_{esco}^{enn}$	Profit of the ESCO under ENN scenario
ENN	Endogenization of unit savings and non-coordination	$\Pi^{ENCO}$	Channel profit under ENCO scenario
EXCO	Exogenous unit savings and centralized control	$\prod_{m,s}^{ENC}$	Profit of the manufacturer under ENC scenario
ENCO	Endogenization of unit savings and centralized control	$\Pi_{ESCO}^{ENC}$	Profit of the ESCO under ENC scenario
EXC ENC	Exogenous unit savings and coordination Endogenization of unit savings and coordination	1 IESCO	From of the ESCO under ENC scenario
ENC	Endogenization of unit savings and coordination	Decision	n variables
Model parameters		$q_i$	Production quantity under EXN scenario
$p_e$	Energy price	$\hat{\theta}$	Fraction of unit savings under EXN scenario
$r_0$	Unit initial energy level	$q^{EXCO}$	Channel production quantity under EXCO scenario
а	Potential market capacity	$r_b^{EN}$	Unit savings under EN scenario
$T_s$	Agreed contract term	$r_s^{ENN}$	Unit savings under ENN scenario
$r_i^{EX}$	Unit savings under EX scenario	φ	Fraction of unit savings under ENN scenario
k <sub>i</sub>	Marginal cost of unit savings under EX scenario	r <sup>ENCO</sup>	Unit savings under ENCO scenario
$p_i$	Retail price under EX scenario	$r_s^{ENC}$	Unit savings under ENC scenario
c	Unit production cost expect unit energy cost	$\varphi_{s}^{ENC}$	Fraction of unit savings of the manufacturer under ENC
λ	Revenue fraction of the manufacturer under EXC	13	scenario
δ	scenario Sansisivity parameter of the domand to the rotail price	$\gamma_s^{ENC}$	Fraction of the investment cost of the manufacturer
ο α	Sensitivity parameter of the demand to the retail price Investment cost coefficient ratio of the ESCO to the	13	under ENC scenario
u	manufacturer		
D	Demand of the manufacturer	Supersc	
k	Investment cost factor of the manufacturer under EN	*	Optimal value
	scenario	·	
р	Retail price under EN scenario	Subscrip	ots Manufacturer
$\prod_{m,b}^{EX}$	Profit of the manufacturer under EX scenario	m ESCO	Energy service company
$\prod_{m,s}^{EXN}$	Profit of the manufacturer under EXN scenario	e	Energy
$\Pi_{ESCO}^{EXN}$	Profit of the ESCO under EXN scenario	i	Set of energy saving modes
$\Pi^{ESCO}$		b	Self saving
	Channel profit under EXCO scenario	S	Shared savings
$\prod_{m,s}^{EXN}$	Profit of the manufacturer under EXC scenario		-

being implemented.

To make up for deficiencies when manufacturers choose self saving, manufacturers can outsource their energy services to energy service companies (ESCOs). Typically, the main form of energy services provided by ESCOs is energy performance contracting (EPC). The EPC is a new market mechanism where a manufacturer outsources energy services to an ESCO, which pays for the investment costs of energy efficiency projects by reducing energy costs and provides the manufacturer with comprehensive energy services from energy audits, investments in equipment, equipment selection, and all aspects of operation and maintenance. According to a survey of 65 foundries in France, Italy, Germany, and seven other countries, approximately 25% of responding enterprises prefer EPC to self saving [5]. There are two general types of performance contracts used in the ESCO industry – shared savings and guaranteed savings [6]. In a shared savings contract, the ESCO provides the financing, and the client assumes no financial obligation other than paying a given share of the materialized savings to the ESCO over a prescribed period of time (we call this an agreed contract term). After the agreed contract term, the customer retains all the savings. Alternatively, in a guaranteed savings contract, projects are often financed by third-party financial entities; the customer repays the loan to the creditor, and the ESCO guarantees a level of savings sufficient to cover the annual debt obligation, thus limiting the customer's performance risk. The shared savings approach is more suitable in developing countries, where energy efficiency projects lack a reliable and commercially viable means of financing, and energy-intensive customers always pursue shortterm economic benefits and are reluctant to invest in energy efficiency projects. In China, shared savings is widely used, as government support for this approach is an important impetus in addition to the above-mentioned reasons. For example, both the tax cut policy released in 2010 and the financial incentives policy released in 2011 clearly require the use of shared savings; there are no similar policies to support guaranteed savings in China [7]. Therefore, we only consider shared savings in this paper.

Comparing self saving with shared savings, an ESCO always has an advantage with regard to the specialty of improving energy efficiency. For example, the ESCO always has more advanced energysaving technologies than the manufacturer for long-term research. To obtain more unit savings, the manufacturer may consider outsourcing energy service to the ESCO. However, the more effective the technology is, the more expensive it is [8,9]. It is an important factor that the manufacturer chooses the optimal energy saving mode between the two types of energy saving modes. Furthermore, when the manufacturer chooses shared savings, if the energy-saving supply chain with the manufacturer and the energy service company is not coordinated, they make decentralized decisions. In a decentralized system, channel performance could be even worse because of the differing and usually conflicting

# دريافت فورى 🛶 متن كامل مقاله

- امکان دانلود نسخه تمام متن مقالات انگلیسی
   امکان دانلود نسخه ترجمه شده مقالات
   پذیرش سفارش ترجمه تخصصی
   امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
   امکان دانلود رایگان ۲ صفحه اول هر مقاله
   امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
   دانلود فوری مقاله پس از پرداخت آنلاین
   پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات
- ISIArticles مرجع مقالات تخصصی ایران