Contents lists available at ScienceDirect





Energy Conversion and Management

journal homepage: www.elsevier.com/locate/enconman

Energetic and exergetic analysis of integrated energy system based on parametric method



Zishuo Huang^{a,b}, Hang Yu^{a,c}, Xiangyang Chu^c, Zhenwei Peng^{a,b,*}

^a Key Laboratory of Ecology and Energy Saving Study of Dense Habitat (Tongji University), Ministry of Education, China

^b College of Architecture and Urban Planning Tongji University, Siping Road No. 1239, Shanghai 200092, China

^c School of Mechanical Engineering Tongji University, Caoan Road No.4800, Shanghai 201804, China

ARTICLE INFO

Keywords: Integrated energy system Energy efficiency Exergy efficiency Parametric analysis

ABSTRACT

Investigating the relationship between the performance of an integrated energy system (IES) and each influencing factor as well as directly calculating IES efficiency based on relevant parameters are of substantial importance to energy saving. To make the research results applicable to various IES, a typical integrated energy system (TIES) which includes typical energy conversion technologies is proposed. After building energy demands and energy conversion processes in TIES are abstracted and simplified by a typical energy flow map, a dimensionless equation for calculating TIES energy and exergy efficiency is developed. Based on the partial derivatives analysis of TIES's energy and exergy efficiency dimensionless equation, the effects of technological level, demand structure, local renewable energy utilization and IES configuration on energy and exergy efficiency are clarified. Combined with a case study, the usability of the parameter analysis method for IES has been illustrated. The departure phenomenon of energetic and exergetic analysis results in IES are also introduced. Furtherly, we indicate that without proper definition of benchmark environment, it is easy to give perplexing results with an exergetic analysis about IES.

1. Introduction

An integrated energy system (IES) converts various types of energy resource (gas, electricity, solar, wind, etc.) into cooling energy, heat and power to meet the production and living needs of building users. To improve IES's energy efficiency, it is important to determine the factors that affect the system and how they affect the system's energy efficiency [1].

The analysis of various energy conversion and utilization processes in IESs has been a perennial focus of researchers in this field [2].According to Perez-Lombard et al., energy efficiency is a core issue of energy policy and sustainable development, and energy efficiency indicators should be established for building energy systems at four levels (e.g., global, service, subsystem and equipment) to construct an efficiency indicator system to improve the energy efficiency of such systems[3].The energy efficiency of gas-fired boilers by employing a device with integrated functions that uses boiler waste heat to drive absorption heat pumps improved by Qu [4].An energy flow map for heating, ventilation and air conditioning systems, the map depicts the flow of energy from the cooling/heating sources to the transport pipeline network and finally to the terminal air conditioning units created by Perez-Lombard [5]. Several common European metrics for measuring the energy efficiency of building energy supply systems introduced by Alves [6]. Alves also provided several common parameters that characterize energy efficiency, including a coefficient of performance and energy efficiency ratio. Kaya analyzed the energy efficiency of heat pumps and determined the relationships between the energy efficiency of a heat pump and the influencing factors (including the flow rate of the refrigerant, pressure and temperature) [7]. Willem reviewed the experimental research on measuring the energy efficiency of heat pump for hot water in practical use and noted that most heat pumps' operated efficiency in a range of 1.8-2.5[8]. Park presented an analytical review of the research on the energy and exergy efficiency of several common renewable energy utilization systems (including solar water heating systems, solar photovoltaic systems and biomass cook stoves), they noted that most of the research was focused on the energy efficiency of these systems, whereas system exergy efficiency was less frequently studied [9].

Research has shown that multiple energy conversion and utilization technologies can be combined to compensate for the deficiency of each conversion and utilization technology, improve a system's total energy and exergy efficiency (η_{total}) and increase the utilization of renewable

http://dx.doi.org/10.1016/j.enconman.2017.08.026

^{*} Corresponding author at: College of Architecture and Urban Planning Tongji University, Siping Road No. 1239, Shanghai 200092, China. *E-mail address*: pengzhw@tongji.edu.cn (Z. Peng).

Received 6 April 2017; Received in revised form 7 August 2017; Accepted 9 August 2017 0196-8904/ @ 2017 Elsevier Ltd. All rights reserved.

| Nomenclature | | | demand |
|--------------|---|---------------|---|
| | | Z | the ratio of the heat demand to the fixed power demand |
| IES | integrated energy system | EX | exergy |
| TIES | typical integrated energy system | Т | temperature |
| HVAC | heating, ventilation and air conditioning | Q | the quantity of energy |
| F | fuel | | |
| CHP | combined heating and power system | Subscript | |
| В | biomass energy | | |
| Е | electricity | total | the overall system |
| S | solar energy | in | input |
| W | wind energy | boil | boiler |
| R, r | local renewable energy resource | fuel | fuel |
| COP | energy coefficient of absorption and mechanical heat | e | electricity |
| | pump | CHP,h | combined heating and power system for heating |
| EER | energy efficient of heat pump for cooling | CHP,e | combined heating and power system for electricity |
| D' | system energy demand | h | heating |
| D | energy supplied by IES, contain the energy export to ex- | с | cooling |
| | ternal | e,0 | electricity for non-heating and non-cooling system con- |
| EX | energy exchange with external | | sumed |
| t | the ratio of the cooling energy provided by the electrical | en | environment |
| | cooling technology to the total cooling energy demand | | |
| v | ratio of the heat provided by the electrical heating tech- | Greek symbols | |
| | nology (including electrical heating and various types of | | |
| | power-driven heat pump) to the total heat demand | η | energy efficiency |
| х | the ratio of the amount of fuel consumed by the boiler in a | θ | the standard coal conversion coefficient for the input fossil |
| | IES to the amount of fuel consumed by the CHP equipment | | fuel and the power |
| у | the ratio of the cooling energy demand to the fixed power | Ω | energy quality, from 0 to 1 |
| | · · · · · · · · · · · · · · · · · · · | | |
| | | | |

energy resources [10]. Duić introduced the strength of IES for islet combined with a case study in Porto Santo [11]. Therefore, IES which employ the combination of multiple energy conversion and utilization technologies have garnered extensive attention. Koirala reviewed the trend and key issues of IES [12]. Lund discussed the impact of IES for district heating and put forward the conception of 4th generation district heating [13]. Hemmes described the characteristics of multisource, multi-energy product integrated energy systems [14]. Di Somma discussed the operation optimization of a distributed energy system based on the comprehensive optimal of exergy efficiency and cost [15]. Al-Ali analyzed the energy and exergy efficiency of a solar–geothermal–combined heat and power (CHP)-coupled system and found that the coupled system outperformed the CHP system in energy and exergy efficiency [16]. Wang analyzed the energy and exergy efficiency of a biomass gas-fueled combined cooling, heat and power (CCHP) system [17]. Mohammadi studied the energy and exergy efficiency of a wind energy coupled with compressed air energy storage systems for heating, cooling and supply power [18], from sensitivity analysis they indicated that parameters related to gas turbine are the most prominent parameters of the system's performance.

Fig. 1. System level focused on in this article.

| Energy efficiency of Equipment | material configuration parameter Boiler Heat Gas-powered Boiler Heat Gas-powered | r setting manufacturing Other factors | | |
|---|--|--|--|--|
| Discussion object Energy efficiency of | Energy equipment | Comprehensive | | |
| integrated energy supply system | Integrated energy supply system: n | nultiple combination of different energy n technologies | | |
| Energy efficiency of | Energy transport system | Air conditioning terminal system | | |
| system | HVAC system | | | |

دريافت فورى 🛶 متن كامل مقاله

- امکان دانلود نسخه تمام متن مقالات انگلیسی
 امکان دانلود نسخه ترجمه شده مقالات
 پذیرش سفارش ترجمه تخصصی
 امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 امکان دانلود رایگان ۲ صفحه اول هر مقاله
 امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 دانلود فوری مقاله پس از پرداخت آنلاین
 پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات
- ISIArticles مرجع مقالات تخصصی ایران