### **Accepted Manuscript**

Thermodynamic analysis for a concentrating photovoltaic-photothermochemical hybrid system

ENERBY

Yangjie Wang, Qiang Li, Dianhong Li, Hui Hong

PII: S0360-5442(18)30210-X

DOI: 10.1016/j.energy.2018.01.182

Reference: EGY 12294

To appear in: Energy

Received Date: 14 August 2017

Revised Date: 03 January 2018

Accepted Date: 31 January 2018

Please cite this article as: Yangjie Wang, Qiang Li, Dianhong Li, Hui Hong, Thermodynamic analysis for a concentrating photovoltaic-photothermochemical hybrid system, *Energy* (2018), doi: 10.1016/j.energy.2018.01.182

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

#### **ACCEPTED MANUSCRIPT**

#### Thermodynamic analysis for a concentrating photovoltaic-

#### 2 photothermochemical hybrid system

- 3 Yangjie Wang<sup>a</sup>, Qiang Li<sup>a,\*</sup>, Dianhong Li<sup>a</sup>, Hui Hong<sup>b</sup>
- 4 aSchool of Energy and Power Engineering, Nanjing University of Science & Technology, Nanjing
- 5 210094, China
- 6 bInstitute of Engineering Thermophysics, Chinese Academy of Sciences, Beijing 100080, China

7

9

10

11

12

13

14

15

16

17

18

19

20

1

#### 8 Abstract

In this paper, a novel model of a concentrating photovoltaic-photothermochemical (CPV/PTC) hybrid system is proposed. Solar spectrum is seperated into several parts to enable photovoltaic (PV) and photothermochemical (PTC) conversion by utilizing the parabolic trough concentrator with a spectral beam splitter. The PV module converts a specific spectral range of solar radiation into electricity directly by the solar cells and the PTC module absorbs the rest solar energy to supply the reaction heat of methanol-steam reforming (MSR) that produces hydrogen for power generation. The energy and exergy analyses on the CPV/PTC hybrid system are carried out. The overall system efficiencies with different splitting wavebands, widths of the solar cells and heat transfer coefficients of the cooling system are investigated. Moreover, the CPV/PTC hybrid system is compared with a single PV or PTC system. The results indicate that the optimal splitting waveband, concentration ratio and heat transfer coefficient of the cooling system are 450nm-870nm, 7.9, and 1500 W/(m²·K), respectively. With the optimization of the proposed CPV/PTC hybrid system, the overall power generation efficiency can reach 25.3%.

<sup>\*</sup> Corresponding author. E-mail address: liqiang@mail.njust.edu.cn (Q. Li)

# دريافت فورى ب

## ISIArticles مرجع مقالات تخصصی ایران

- ✔ امكان دانلود نسخه تمام متن مقالات انگليسي
  - ✓ امكان دانلود نسخه ترجمه شده مقالات
    - ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
  - ✓ امكان دانلود رايگان ۲ صفحه اول هر مقاله
  - ✔ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
    - ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات