

Accepted Manuscript

Technical assessment of electric heat boosters in low-temperature district heating based on combined heat and power analysis

Hanmin Cai, Shi You, Jiawei Wang, Henrik W. Bindner, Sergey Klyapovskiy



PII: S0360-5442(18)30312-8

DOI: [10.1016/j.energy.2018.02.084](https://doi.org/10.1016/j.energy.2018.02.084)

Reference: EGY 12384

To appear in: *Energy*

Received Date: 1 November 2017

Revised Date: 23 January 2018

Accepted Date: 17 February 2018

Please cite this article as: Cai H, You S, Wang J, Bindner HW, Klyapovskiy S, Technical assessment of electric heat boosters in low-temperature district heating based on combined heat and power analysis, *Energy* (2018), doi: 10.1016/j.energy.2018.02.084.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Technical Assessment of Electric Heat Boosters in Low-Temperature District Heating based on Combined Heat and Power Analysis

Hanmin Cai^a, Shi You^{a,*}, Jiawei Wang^a, Henrik W. Bindner^a, Sergey Klyapovskiy^a

^a*Technical University of Denmark, 2800 Kgs. Lyngby, Denmark*

Abstract

This paper provides a technical assessment of electric heat boosters (EHBs) in low-energy districts. The analysis is based on a hypothetical district with 23 terraced single-family houses supplied by both a low-temperature district heating (LTDH) network and a low-voltage network (LVN). Two case studies are provided to show the active role of EHBs in a smart energy system (SES). The first case compares annual heat and power flow analyses for LTDH at five supply temperature levels, focusing on their impacts. The results show that district heating network (DHN) losses can be reduced by 35% if the supply temperature is reduced from 70 °C to 50 °C, but the LVN peak power will have to be increased by up to 2% using heat boosting. The second case further aggregates EHBs to provide a fuel shift (FS) service for the DHN. The results show that while LVN peak power was increased by up to 4.3%, the basic power production and peak boiler usage for DHN could be reduced by as much as 15% and 48%, respectively. In summary, lower supply temperatures and intelligent components can improve system efficiency and turn the DHN into an integrated part of a SES.

Keywords: Smart energy systems; 4GDH; Low-temperature district heating; Electric heat boosters; Fuel shift; Combined heat and power.

1. Introduction

Denmark is aiming at a 100% renewable-based electricity and heating sector by 2035 and a complete transition to a renewable-based energy system by 2050 [1]. Such ambitious targets demand considerable effort involving integration of intermittent renewable sources and energy conservation. In recent years, a large number of renewable energy sources, such as wind power plants, have been connected to the Danish energy system. Meanwhile, energy

*Corresponding author

Email addresses: hacai@elektro.dtu.dk (Hanmin Cai), sy@elektro.dtu.dk (Shi You), jiawang@elektro.dtu.dk (Jiawei Wang), hwbi@elektro.dtu.dk (Henrik W. Bindner), seklya@elektro.dtu.dk (Sergey Klyapovskiy)

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات