

## Accepted Manuscript

Effects of melt-pool geometry on microstructure structural damage behavior for single crystal superalloys in rapid solidification process

Tao Dong, Chentong Gao, Haozhang Hou, Yanling Pei, Shusuo Li, Shengkai Gong

PII: S0142-1123(18)30083-5

DOI: <https://doi.org/10.1016/j.ijfatigue.2018.02.035>

Reference: JIJF 4600

To appear in: *International Journal of Fatigue*

Received Date: 13 November 2017

Revised Date: 24 February 2018

Accepted Date: 26 February 2018

Please cite this article as: Dong, T., Gao, C., Hou, H., Pei, Y., Li, S., Gong, S., Effects of melt-pool geometry on microstructure structural damage behavior for single crystal superalloys in rapid solidification process, *International Journal of Fatigue* (2018), doi: <https://doi.org/10.1016/j.ijfatigue.2018.02.035>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



**Effects of melt-pool geometry on microstructure structural damage  
behavior for single crystal superalloys in rapid solidification process**

Tao Dong, Chentong Gao, Haozhang Hou, Yanling Pei, Shusuo Li, Shengkai Gong\*

School of Materials Science and Engineering, Beihang University, No. 37 Xueyuan

Road, Beijing, 100191, PR China

\*Corresponding author.

Tel.: +86 10 82314488; fax: +86 10 82338200.

E-mail address: [gongsk@buaa.edu.cn](mailto:gongsk@buaa.edu.cn) (S. Gong)

**Abstract:** Electro-machining surface stochastic failure is one of the main factors which limit the use of electrical discharge machining in hot end of aeronautics and astronautics. This study proposes the recast layer (RL) failure prediction model and analyses the effect of unit melt-pool geometry on recast layer structural stability in single crystal by analyzing cellular-dendrite microstructure around ring layer. Both model calculation and experimental results show that melt-pool geometry parameters-radius-depth ratio and tangent angle directly influence ring RL thermal structural stability. Smaller radius-depth ratio range and larger tangent angle (on (100) substrate) can significantly improve RL performance or even avoid high temperature service structural damage. For certain undesirable melt-pool geometry, the RL damage crack location has selectivity on specific secondary orientation. High temperature oxidation, crack initiation and propagation mode together influence RL failure modes in high temperature atmospheric environment. Electro-machining surface reliability can be effectively evaluated with the prediction model, and the geometry parameters can be used to provide efficient data for surface structure design.

**Keywords:** Rapid solidification microstructure; Single crystal superalloys; Melt-pool geometry; Secondary orientation; Thermal fatigue

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات