

Accepted Manuscript

Competitive siloxane adsorption in multicomponent gas streams for biogas upgrading

Alba Cabrera-Codony, Eric Santos-Clotas, Conchi O. Ania, Maria J. Martín

PII: S1385-8947(18)30489-3
DOI: <https://doi.org/10.1016/j.cej.2018.03.131>
Reference: CEJ 18738

To appear in: *Chemical Engineering Journal*

Received Date: 25 January 2018
Revised Date: 22 March 2018
Accepted Date: 23 March 2018

Please cite this article as: A. Cabrera-Codony, E. Santos-Clotas, C.O. Ania, M.J. Martín, Competitive siloxane adsorption in multicomponent gas streams for biogas upgrading, *Chemical Engineering Journal* (2018), doi: <https://doi.org/10.1016/j.cej.2018.03.131>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Competitive siloxane adsorption in multicomponent gas streams for biogas upgrading

Alba Cabrera-Codony¹, Eric Santos-Clotas¹, Conchi O. Ania², Maria J. Martín^{1*}

¹LEQUIA. Institute of Environment. University of Girona, Campus Montilivi, Girona, Catalonia, Spain.

²POR2E Group, CEMHTI (UPR 3079) CNRS, Univ. Orléans, Orléans 45071, France.

*Corresponding author: E-mail address: maria.martin@udg.edu, Tel: +34972418161

Abstract

Biogas, produced in anaerobic digesters, is used as a renewable fuel after undergoing several upgrading processes. Adsorption onto activated carbon is the most widely used technology to remove harmful volatile compounds, such as siloxanes. However, the competition for the adsorptive sites with other biogas impurities reduces the performance of the adsorbents increasing the operative costs.

This work studies the competitive adsorption of volatile organic compounds and siloxanes into activated carbons of different sources and activation processes. Ten selected materials were exhaustively characterized in terms of textural and chemical properties. Dynamic competitive adsorption tests displayed different equilibrium uptakes for each target compound depending on the properties of each carbon type. Chemically activated carbons demonstrated a higher adsorption capacity and higher selectivity for bulky siloxanes, being the most suitable adsorbents for biogas upgrading. The performance of the adsorbents was also investigated in the presence of moisture, which enable siloxane hydrolysis reactions in the carbon surface, leading to the formation of α - ω -silanediols, especially on phosphoric acid-activated carbons.

The technical implications of this work are discussed in terms of biogas volume treated per volume of adsorbent at the first siloxane breakthrough. Phosphoric acid activated carbons are capable of treating higher number of bed volumes, reducing the costs associated to the adsorbent replacement.

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات