Accepted Manuscript

Inherently safer design for heat exchanger network

Mohsin Pasha, Dzulkarnain Zaini, Azmi Mohd Shariff

PII: S0950-4230(17)30334-0 DOI: 10.1016/j.jlp.2017.04.002


Reference: JLPP 3467

To appear in: Journal of Loss Prevention in the Process Industries

Received Date: 27 April 2016
Revised Date: 11 March 2017
Accepted Date: 2 April 2017

Please cite this article as: Pasha, M., Zaini, D., Mohd Shariff, A., Inherently safer design for heat exchanger network, *Journal of Loss Prevention in the Process Industries* (2017), doi: 10.1016/j.jlp.2017.04.002.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



ACCEPTED MANUSCRIPT

INHERENTLY SAFER DESIGN FOR HEAT EXCHANGER NETWORK

Mohsin Pasha a, Dzulkarnain Zaini a, Azmi Mohd Shariff a*

^aCentre for Advance Process Safety (CAPS), Chemical Engineering Department, Universiti Teknologi PETRONAS,

32610 Seri Iskandar, Perak, Malaysia

*Corresponding Author: azmish@petronas.com.my (A.M. Shariff)

Phone: +60 05 3687570 Fax: +06 05 3656176

Abstract

The failure of shell and tube heat exchangers is a chronic problem in the chemical process industries. Meager safety

analysis and lack of inherently safer design considerations are noticeable issues resulting in the failure of these heat

exchangers. Existing inherent safety level quantification methods mostly focus on the process route selection in the

preliminary design stage. Nevertheless, existing methods have never been applied to quantify the inherent safety

level in a heat exchanger network. Therefore, this paper presents a coherent framework to outline an inherently safer

heat exchanger network in the preliminary design stage. In this framework, newly developed safety indices are

introduced to estimate the inherent safety level of a single heat exchanger and the heat exchanger network. The

worst heat exchanger is identified based on the lowest inherent safety level. An inherent risk assessment (IRA) of

the worst heat exchanger is carried out to analyze the inherent risk of potential explosion event. Moreover, normal

distribution of the safety index values is analyzed through the normality test. Inherent risk assessment and the

normal distribution of index values are configured as a decision-making steps for implementing the inherently safer

design strategies. This framework is integrated with a process design simulator (Aspen HYSYS) for seamless

transfer of the process information. A heat exchanger network of a typical ammonia synthesis loop was considered

as a case study. Inherently safer designs for this heat exchanger network are presented by using moderation and

simplification methods. The inherent safety level of the heat exchanger network can be improved by applying

inherently safer design strategies.

Keywords; inherent safety level, inherently safer design, heat exchanger network, preliminary design stage, process

design simulator.

1

دريافت فورى ب

ISIArticles مرجع مقالات تخصصی ایران

- ✔ امكان دانلود نسخه تمام متن مقالات انگليسي
 - ✓ امكان دانلود نسخه ترجمه شده مقالات
 - ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 - ✓ امكان دانلود رايگان ۲ صفحه اول هر مقاله
 - ✔ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 - ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات