Accepted Manuscript

Optimization of thermal management system for Li-ion batteries using phase change material

Yantong Li, Yaxing Du, Tao Xu, Huijun Wu, Xiaoqing Zhou, Ziye Ling, Zhengguo Zhang


PII: S1359-4311(17)36609-7

DOI: https://doi.org/10.1016/j.applthermaleng.2017.12.055

Reference: ATE 11576

To appear in: Applied Thermal Engineering

Received Date: 15 October 2017 Revised Date: 21 November 2017 Accepted Date: 14 December 2017



Please cite this article as: Y. Li, Y. Du, T. Xu, H. Wu, X. Zhou, Z. Ling, Z. Zhang, Optimization of thermal management system for Li-ion batteries using phase change material, *Applied Thermal Engineering* (2017), doi: https://doi.org/10.1016/j.applthermaleng.2017.12.055

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

Optimization of thermal management system for Li-ion batteries using phase change material

Yantong Li^a, Yaxing Du^b, Tao Xu^{c, *}, Huijun Wu^c, Xiaoqing Zhou^c, Ziye Ling^d, Zhengguo

$Zhang^{d}$

- ^a Department of Architecture and Civil Engineering, City University of Hong Kong, Tat Chee Avenue, Kowloon, Hong Kong
- ^b Department of Building Services Engineering, The Hong Kong Polytechnic University, Hung Hom, Kowloon, Hong Kong
- ^c School of Civil Engineering, Guangzhou University, Guangzhou 510006, China
- ^d Key Laboratory of Enhanced Heat Transfer and Energy Conservation, The Ministry of Education, School of Chemistry and Chemical Engineering, South China University of Technology, Guangzhou 510640, China

ABSTRACT

This study presents an optimization method of Li-ion battery thermal management system (BTMS) using phase change material (PCM). The optimization objective is to minimize the mass of PCM. Two design constraints should be satisfied during the optimization process: (1) the maximum temperature difference in the BTMS should not exceed the threshold value; (2) the desired working time of maintaining the batteries temperature under operation safe temperature should be fulfilled. A case study of the cylindrical BTMS with PCM is selected to illustrate the proposed optimization method. The expanded graphite (EG)/ paraffin (PA) composite PCM is used in the BTMS. The thermodynamic mathematical models of the system are solved by the commercial software computational fluid dynamics (CFD). The numerical results are validated against experimental data, and a good agreement has been achieved. During the optimization, four types of BTMS which respectively use single, double, three and four batteries, are considered. The effects of battery radius, gap between neighboring batteries, heat generation rate, and top and bottom PCM thickness on the minimum mass of PCM are analyzed. The optimal radiuses of the PCM unit in different conditions are identified. Results indicate that the proposed optimization method is effective

^{*}The corresponding author; Email: cetxu@scut.edu.cn

دريافت فورى ب متن كامل مقاله

ISIArticles مرجع مقالات تخصصی ایران

- ✔ امكان دانلود نسخه تمام متن مقالات انگليسي
 - ✓ امكان دانلود نسخه ترجمه شده مقالات
 - ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 - ✓ امكان دانلود رايگان ۲ صفحه اول هر مقاله
 - ✔ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 - ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات