

Accepted Manuscript

A numerical study of the effect of single overloads on plasticity induced crack closure

J.B. Baptista, F.V. Antunes, L. Correia, R. Branco

PII: S0167-8442(16)30179-3

DOI: <http://dx.doi.org/10.1016/j.tafmec.2016.12.001>

Reference: TAFMEC 1790

To appear in: *Theoretical and Applied Fracture Mechanics*

Received Date: 1 July 2016

Revised Date: 7 November 2016

Accepted Date: 6 December 2016

Please cite this article as: J.B. Baptista, F.V. Antunes, L. Correia, R. Branco, A numerical study of the effect of single overloads on plasticity induced crack closure, *Theoretical and Applied Fracture Mechanics* (2016), doi: <http://dx.doi.org/10.1016/j.tafmec.2016.12.001>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



A numerical study of the effect of single overloads on plasticity induced crack closure

JB Baptista⁽¹⁾, FV Antunes^{* (1)}, L Correia⁽²⁾, R Branco⁽³⁾

⁽¹⁾ CEMUC, Department of Mechanical Engng, University of Coimbra, Rua Luís Reis Santos, Pinhal de Marrocos, 3030-788 Coimbra, Portugal

⁽²⁾ CEMUC, Escola Superior de Tecnologia do Instituto Politécnico de Castelo Branco, Av. do Empresário, 6000 - 767 Castelo Branco

⁽³⁾ CEMUC, Depart. of Mechanical Engineering, Polytechnic Institute of Coimbra, 3030-129 Coimbra, Portugal

Abstract

In this work, the effect of single overloads on plasticity induced crack closure is studied. An elastic-plastic finite element model was developed and the crack opening level was calculated from the contact forces along the crack flank. The effects of the loading parameters and stress state are analysed, and the mechanisms behind crack closure variations are identified. An overload is a traumatic event that eliminates material's memory relative to the load history. Crack tip blunting is the mechanism behind this memory loss, since it eliminates crack closure. Material hardening has a major relevance on the evolution of plastic blunting, which was evident in the variation of the CTOD parameter. On the other hand, the overload produces strong plastic deformation ahead of the crack tip, giving rise to conditions for the rapid generation of crack closure higher than before the event. The peak of crack closure was found to increase linearly with the load increase above the maximum baseline value. The crack is totally closed for overload ratios of about 2.5. Empirical models were developed for the peak of crack closure, for the delay of this peak and for the stabilization distance after the overload. Finally, the stress state was found to have a major effect on crack closure level after an overload.

Keywords: plasticity induced crack closure; overload; blunting; residual plastic deformation; finite element method

* Corresponding author. Tel.: 351-239-790700; Fax 351-239-790701; E-mail: fernando.ventura@dem.uc.pt

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات