

Accepted Manuscript


Title: Algorithms for Smart Grid Management

Author: R. Marah A. El Hibaoui

PII: S2210-6707(17)30729-1

DOI: <https://doi.org/doi:10.1016/j.scs.2018.01.041>

Reference: SCS 954



To appear in:

Received date: 27-6-2017

Revised date: 3-12-2017

Accepted date: 22-1-2018

Please cite this article as: R. Marah, A. El Hibaoui, Algorithms for Smart Grid Management, *Sustainable Cities and Society* (2018), <https://doi.org/10.1016/j.scs.2018.01.041>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Algorithms for Smart Grid Management

R. Marah^a, A. El Hibaoui^{a,*}

^a*FS- Abdelmalek Essaâdi University
P.O. Box. 2121 M'Hannech II
93030 Tetuan Morocco*

Abstract

In this paper, we will consider a modelization of Smart Grid on three sub-components: local level, microgrid level and $T&D$ level. Thus and on one hand, we will propose an algorithm that manages its local level. Our algorithm is paired with Branch and Bound algorithm to solve Knapsack Problem. The main goal of this algorithm is to regulate consumption peaks and manage the priority of domestic appliances, by spreading at best the energy depending on the priority and consumption without exceeding the total energy received.

Furthermore, we will introduce an asynchronous distributed max-flow algorithm to resolve the routing problem in order to optimize the $T&D$ level. This algorithm uses a local computation to compute max-flow. Nodes communicate only by exchanging messages and no global information is needed. Our algorithm uses more than one augmenting path at each iteration allowing optimization of the execution time required for computing the max-flow.

Keywords: Smart Grid Modelization, Knapsack Problem, Branch and Bound Algorithm, Routing Problem, Distributed Max-Flow Algorithm, Optimization

1. Introduction

Smart Grid is presented as an intelligent power grid to optimize production [1], distribution and consumption of electricity. It helps to balance its delivery and demand through the introduction of the ICT (*Information and*

*Corresponding author
Email address: a.hibaoui@gmail.com (A. El Hibaoui)

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات