Accepted Manuscript

Switch-and-stay combining for energy harvesting relaying systems

Hai Huang, Junjuan Xia, Xin Liu, Zhenyu Na, Qinghai Yang, Hongbin Chen, Junhui Zhao


PII: S1874-4907(18)30021-1

DOI: https://doi.org/10.1016/j.phycom.2018.03.006

Reference: PHYCOM 508

To appear in: Physical Communication

Received date: 14 January 2018 Revised date: 11 March 2018 Accepted date: 13 March 2018



This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



ACCEPTED MANUSCRIPT

Switch-and-Stay Combining for Energy Harvesting Relaying Systems

Hai Huang¹, Junjuan Xia², Xin Liu³, Zhenyu Na⁴, Qinghai Yang⁵, Hongbin Chen⁶, and Junhui Zhao⁷

¹ Department of Computer Science, Guangdong University of Education, China (e-mail:huanghai921@sina.com).

² School of Computer Science and Educational Software, Guangzhou University, China (e-mail: xiajunjuan@gzhu.edu.cn).

³ School of Information and Communication Engineering, Dalian University of Technology, Dalian, China (e-mail:liuxinstar1984@dlut.edu.cn).

⁴School of Information Science and Technology, Dalian Maritime University, Dalian 116026, China (e-mail:nazhenyu@dlmu.edu.cn).

⁵State Key Laboratory on ISN, School of Telecommunications Engineering, Xidian University, Xi'an 710071, China, (e-mail:qhyang@xidian.edu.cn).

⁶ Key Laboratory of Cognitive Radio and Information Processing, Guilin University of Electronic Technology, Guilin, China (email: chbscut@guet.edu.cn).

⁷ School of Information Engineering, East China Jiaotong University, Nanchang, China (email: eeejhzhao@163.com).

Abstract

In this paper, we study the switch-and-stay combining technique into the energy-harvesting relaying networks, where the relay obtains its transmit power from the source through wireless energy harvesting. The moderate shadow environments are applied, so that the data transmission from the source to the destination can go through the direct link. Although the conventional selection combining technique can exploit both the direct and relaying branches for data transmission, it has to require to know the channel parameters of both branches, and results into frequent branch switching. To solve these issues, switch-and-stay combining (SSC) is proposed into the energy-harvesting relay-

¹J. Xia is the corresponding author of this paper. This work was supported by the Innovation Team Project of Guangdong Province University under Grant 2016KCXTD017, by the Foundation for Excellent Young Talents in Higher Education of Guangdong (No. 2015KQNCX109), and by the Research Fund for the Doctoral Program of Guangdong University of Education (No. 2016ARF04).

دريافت فورى ب

ISIArticles مرجع مقالات تخصصی ایران

- ✔ امكان دانلود نسخه تمام متن مقالات انگليسي
 - ✓ امكان دانلود نسخه ترجمه شده مقالات
 - ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 - ✓ امكان دانلود رايگان ۲ صفحه اول هر مقاله
 - ✔ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 - ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات