Accepted Manuscript

Flexible and High Noise Margin Organic Enhacement Inverter Using Hybrid Insulator

Dong-Hoon Lee, Jinsu Kim, Hyeong-Jun Cho, Min Su Kim, Eung-Kyu Park, Nae Eung Lee, Yong-Sang Kim

PII: S0040-6090(16)30806-9 DOI: doi: 10.1016/j.tsf.2016.11.051

Reference: TSF 35653

To appear in: Thin Solid Films

Received date: 10 May 2016
Revised date: 28 November 2016
Accepted date: 28 November 2016



Please cite this article as: Dong-Hoon Lee, Jinsu Kim, Hyeong-Jun Cho, Min Su Kim, Eung-Kyu Park, Nae Eung Lee, Yong-Sang Kim, Flexible and High Noise Margin Organic Enhacement Inverter Using Hybrid Insulator, *Thin Solid Films* (2016), doi: 10.1016/j.tsf.2016.11.051

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

Flexible and High Noise Margin Organic Enhacement Inverter Using Hybrid Insulator

Dong-Hoon Lee^a, Jinsu Kim^b, Hyeong-Jun Cho^a, Min Su Kim^a, Eung-Kyu Park^a, Nae Eung Lee^b, Yong-Sang Kim^{a,*}

athe School of Electronics and Electrical Engineering, Sungkyunkwan University, Suwon, Gyeonggi, 440-746, South Korea
 bthe SKKU Advanced Institute of Nanotechnology (SAINT), Sungkyunkwan University, Suwon, Gyeonggi, 440-746, South Korea

Abstract

We demonstrate a high noise margin and highly flexible enhancement inverter based on the organic-inorganic hybrid insulator. Organic insulators generally show high leakage current and inorganic insulator are brittle. In this work, hybrid insulator was used in pentacene based organic thin film transistors (OTFTs) to overcome the limitations of each single type of insulator. We report highly flexible OTFTs with reduced threshold voltage and negligible hysteresis using a poly(methyl methacrylate)/silicon nitride hybrid insulator. Using the optimized hybrid insulator, we also demonstrate an enhancement inverter which shows high noise margin with noise margin low of 2.2 V, a noise margin high of 14.1 V and gain of 2.1.

Keywords: Thin film transistors, Flexible structures, Electrical engineering, Inverters

 $Email\ address:\ {\tt yongsang@skku.edu}\ ({\tt Yong-Sang}\ {\tt Kim})$

^{*}Corresponding author

دريافت فورى ب

ISIArticles مرجع مقالات تخصصی ایران

- ✔ امكان دانلود نسخه تمام متن مقالات انگليسي
 - ✓ امكان دانلود نسخه ترجمه شده مقالات
 - ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 - ✓ امكان دانلود رايگان ۲ صفحه اول هر مقاله
 - ✔ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 - ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات