

Accepted Manuscript

Fabrication of pristine graphene-based conductive polystyrene composites towards high performance and light-weight

Fangwei Zhao, Guangfa Zhang, Shuai Zhao, Jian Cui, Ailin Gao, Yehai Yan



PII: S0266-3538(17)33051-8

DOI: [10.1016/j.compscitech.2018.02.013](https://doi.org/10.1016/j.compscitech.2018.02.013)

Reference: CSTE 7089

To appear in: *Composites Science and Technology*

Received Date: 30 November 2017

Revised Date: 3 February 2018

Accepted Date: 10 February 2018

Please cite this article as: Zhao F, Zhang G, Zhao S, Cui J, Gao A, Yan Y, Fabrication of pristine graphene-based conductive polystyrene composites towards high performance and light-weight, *Composites Science and Technology* (2018), doi: 10.1016/j.compscitech.2018.02.013.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Fabrication of pristine graphene-based conductive polystyrene composites towards high performance and light-weight

Fangwei Zhao, Guangfa Zhang, Shuai Zhao, Jian Cui, Ailin Gao*, Yehai Yan*

Key Lab of Rubber-plastics, Ministry of Education/Shandong Provincial Key Lab of Rubber-plastics, School of Polymer Science and Engineering, Qingdao University of Science and Technology, Qingdao, 266042, China

* Corresponding author.

E-mail addresses: gaoal@qust.edu.cn, yhyan@qust.edu.cn

Abstract: Although highly electrically conductive polymer composites filled with two-dimensional graphene-based nanofillers have been considerably explored, it still remains a challenge for constructing these nanocomposites with high filler efficiency, mild fabricating condition, as well as more effective conductive network at lower nanofiller contents. To meet above objectives, a facile preparation strategy was designed, wherein the pristine graphene (*pGR*) was utilized as nanofiller in polystyrene (PS) particle matrix via latex technology. Owing to the absence of reduction process, the hot-processing parameters were optimized to be more gentle ones. The structural, morphological, electrical, thermal and mechanical properties of resultant PS/*pGR* nanocomposites with various *pGR* contents were systematically investigated. SEM and TEM images showed the excellent interfacial adhesion between these two materials and segregated conductive structure was well-established. The as-fabricated PS/*pGR* composites achieved a quite high electrical conductivity of 20.5 S/m at a relatively low *pGR* loading of 0.957 vol% and an ultralow electrical percolation threshold of 0.0475

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات