

Accepted Manuscript

Title: Localization Improvement in Wireless Sensor Networks
Using a New Statistical Channel Model

Author: Amir Karimi Alavijeh Mohammad Hossein
Ramezani Ali Karimi Alavijeh



PII: S0924-4247(17)31240-2
DOI: <https://doi.org/doi:10.1016/j.sna.2018.01.015>
Reference: SNA 10570

To appear in: *Sensors and Actuators A*

Received date: 12-7-2017
Revised date: 22-12-2017
Accepted date: 8-1-2018

Please cite this article as: Amir Karimi Alavijeh, Mohammad Hossein Ramezani, Ali Karimi Alavijeh, Localization Improvement in Wireless Sensor Networks Using a New Statistical Channel Model, *Sensors & Actuators: A. Physical* (2018), <https://doi.org/10.1016/j.sna.2018.01.015>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Localization Improvement in Wireless Sensor Networks Using a New Statistical Channel Model

Amir Karimi Alavijeh^{a,*}, Mohammad Hossein Ramezani^b, Ali Karimi Alavijeh^c

^a*Faculty of Electrical Engineering and Computer Science, University of S. Beheshti, Tehran, Iran*

^b*Mads Clausen Institute, Faculty of Engineering, University of Southern Denmark, Sønderborg, Denmark*

^c*Faculty of Electrical Engineering, Azad University of Najafabad, Isfahan, Iran*

Abstract

In this paper, a statistical channel model is proposed based on the second moment of Received Signal Strength Indicator (RSSI) in an outdoor communication channel. The medium under study is a grass field where the RSSI data are collected in different distances and orientations using a set of in-house built transmitter-receiver sensors. The validity of the constructed sensors is confirmed since the first moment of RSSI data follows the well-known Friis model. The proposed model presents an additional relationship between the variance of RSSI data and distance. To demonstrate the application of this statistical relationship, we have investigated the localization problem of a hidden node using extended Kalman filter (EKF). Compared to the conventional EKF in which the covariance matrix of measurement noise is fixed, this matrix can be updated online using the proposed model. The experimental and simulation results of two different scenarios, which are fixed hidden node and mobile hidden node, show that the proposed model improves the accuracy of RSSI localization from 10 to 22 percent in different situations.

Keywords:

Localization, Channel Modeling, Measurement noise, Wireless sensor network, Extended Kalman Filters

*Corresponding author

Email address: amirkarimi@ace.sbu.ac.ir (Amir Karimi Alavijeh)

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات