

## Accepted Manuscript

Title: BUILDING THERMAL DESIGN FOR SOLAR PHOTOVOLTAIC AIR-CONDITIONING IN AUSTRALIAN CLIMATES

Author: M.J. GOLDSWORTHY



PII: S0378-7788(16)31600-0  
DOI: <http://dx.doi.org/doi:10.1016/j.enbuild.2016.11.046>  
Reference: ENB 7161

To appear in: *ENB*

Received date: 20-11-2015  
Revised date: 30-10-2016  
Accepted date: 18-11-2016

Please cite this article as: M.J.GOLDSWORTHY, BUILDING THERMAL DESIGN FOR SOLAR PHOTOVOLTAIC AIR-CONDITIONING IN AUSTRALIAN CLIMATES, Energy and Buildings <http://dx.doi.org/10.1016/j.enbuild.2016.11.046>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# BUILDING THERMAL DESIGN FOR SOLAR PHOTOVOLTAIC AIR-CONDITIONING IN AUSTRALIAN CLIMATES

M.J. GOLDSWORTHY<sup>1</sup>

<sup>1</sup>Commonwealth Scientific and Industrial Research Organisation, Newcastle, Australia  
10 Murray Dwyer Cr. Mayfield West NSW 2304.  
Ph. 61 2 49606112 Email: [mark.goldsworthy@csiro.au](mailto:mark.goldsworthy@csiro.au)

## Highlights

- An off-grid PV-battery air conditioner and building physical model is described
- Simulations are run with varying Australian climates and building types
- Comfort improvement relative to unconditioned buildings is assessed
- Building characteristics and interactions leading to greater comfort are discussed
- Results show a modest sized PV-battery system can produce high levels of comfort

## ABSTRACT

Residential buildings should be places in which their occupants feel comfortable and content. In an energy conscious world the challenge of offering improved indoor comfort is contrast with the desire to minimise grid energy consumption (both from an efficient distribution perspective and to minimise fossil fuel consumption) as well as the associated cost. Occupant behaviour is one of the key drivers of energy consumption, and in particular peak energy consumption, which is largely the result of air-conditioner usage. Selecting the most cost effective building designs or modifications that met these dual goals regardless of occupant behaviour is a non-trivial task. One way of approaching this problem that guarantees no grid connected energy usage is to use an off-grid PV-battery driven air-conditioner. Here we use a detailed simulation model to investigate the suitability of a small off-grid PV-battery system to power an air-conditioner to provide occupant comfort for a range of different building thermal designs across Australian climates. The relative importance of different building parameters on the ability of the off-grid system to provide comfort is discussed. Results show that even in tropical climates, there are certain building thermal designs that lead to indoor temperatures <25°C at all times with a modest size PV-battery system.

**KEYWORDS:** Building thermal design, air-conditioning, photovoltaic, off-grid

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات