Accepted Manuscript

Image processing based characterisation of coal cleat networks

J. Busse, J.R. de Dreuzy, Sergio Galindo Torres, D. Bringemeier, A. Scheuermann

PII: DOI: Reference: S0166-5162(16)30318-4 doi:10.1016/j.coal.2016.11.010 COGEL 2752

To appear in: International Journal of Coal Geology

Received date:23 JuneRevised date:13 NovaAccepted date:13 Nova

23 June 2016 13 November 2016 13 November 2016 Determentante Jerement et COAL GEOLOGY

Please cite this article as: Busse, J., de Dreuzy, J.R., Torres, Sergio Galindo, Bringemeier, D., Scheuermann, A., Image processing based characterisation of coal cleat networks, *International Journal of Coal Geology* (2016), doi:10.1016/j.coal.2016.11.010

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Image processing based characterisation of coal cleat networks

J. Busse *^a, J.R. de Dreuzy ^b, Sergio Galindo Torres^a, D. Bringemeier ^{a,c}, A. Scheuermann ^a

*Corresponding author: j.busse@uq.edu.au, +61 40 1906 327

^a Geotechnical Engineering Centre, School of Civil Engineering, University of Queensland, St. Lucia, QLD, Australia

^b Geosciences Rennes, University Rennes 1, Rennes, Brittany, France

^cGolder Associates Pty Ltd, Milton, QLD, Australia

Abstract

Characterisation of the cleat network serves as the basis for estimating the hydraulic and mechanical seam properties which in turn are fundamental for flow and geomechanical modelling in the context of underground coal mining. Cleat and cleat network geometry can be described as a function of frequency, aperture, size, orientation relative to in situ stresses, connectivity and porosity, with mineralised and un-mineralised cleats occurring. To describe these properties, CT-scans of core samples of a Bowen Basin coal in central Queensland, Australia, are analysed.

A unique image processing workflow method is introduced to extract the key statistical parameters of perpendicular butt and face cleats present in a two-dimensional image. As face and butt cleats have different characteristics, the presented method distinguishes face cleats and butt cleats by direction and present detailed data for both cleat types. The results comprise cleat length, apertures, sizes, intensities, densities, shape parameter, spacing, orientation and connectivity and are therefore more comprehensive than previous cleat descriptions. Three generally different cleat geometries are considered within this study, one sample shows perpendicular face and butt cleats, the second two sets of face cleats intersected by butt cleats and the third parallel face cleats only.

Keywords

cleat geometry, image processing, coal properties, CT scans

1. Introduction

1.1. Coal cleat networks

Coal is characterised by its unique microstructure of a low permeable porous matrix intersected by a network of face and butt cleats. Cleats are natural opening-mode fractures within coal beds. Together with fault related and mining induced large-scale fractures, these small scale cleats provide the principal source of permeability for groundwater and gas flow within the seam (Laubach et al., 1998). In contrast to the fractures, the smaller systematic cleats do not cut clastic facies adjacent to the coal layers (Dron 1925). Cleats are distinguished by their orientation into two types (Figure 1a). Face cleats are dominant and are directed perpendicular to the bedding plane. The fewer orthogonal butt cleats generally terminate when they encounter face cleats (Laubach et al., 1998). Butt cleats are thought to accommodate relaxation of the stress which originally formed the face cleats. This leads to perpendicularity between both cleat types (Golab et al. 2013). Most research has been done on this orthogonal cleat system. For example, Robertson & Christiansen (2008) described the cleat system as a system consisting of cubic matrix blocks. However, Nick et al., 1995 observed more complex structure systems which need to be characterised differently. A variety of cleat patterns in

دريافت فورى 🛶 متن كامل مقاله

- امکان دانلود نسخه تمام متن مقالات انگلیسی
 امکان دانلود نسخه ترجمه شده مقالات
 پذیرش سفارش ترجمه تخصصی
 امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 امکان دانلود رایگان ۲ صفحه اول هر مقاله
 امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 دانلود فوری مقاله پس از پرداخت آنلاین
 پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات
- ISIArticles مرجع مقالات تخصصی ایران