

Accepted Manuscript

Determination of geological strength index of jointed rock mass based on image processing.

Kunui Hong, Eunchol Han, Kwangsong Kang

PII: S1674-7755(16)30122-6

DOI: [10.1016/j.jrmge.2017.05.001](https://doi.org/10.1016/j.jrmge.2017.05.001)

Reference: JRMGE 350

To appear in: *Journal of Rock Mechanics and Geotechnical Engineering*


Received Date: 6 September 2016

Revised Date: 20 April 2017

Accepted Date: 10 May 2017

Please cite this article as: Hong K, Han E, Kang K, Determination of geological strength index of jointed rock mass based on image processing., *Journal of Rock Mechanics and Geotechnical Engineering* (2017), doi: 10.1016/j.jrmge.2017.05.001.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Determination of geological strength index of jointed rock mass based on image processing

Kunui Hong^{1,*}, Eunchol Han², Kwangsong Kang¹

1. Faculty of Mining Engineering, Kim Chaek University of Technology, Pyongyang, Democratic People's Republic of Korea

2. School of Engineering and Science, Kim Chaek University of Technology, Pyongyang, Democratic People's Republic of Korea

Abstract: The geological strength index (GSI) system, widely used for the design and practice of mining process, is a unique rock mass classification system related to the rock mass strength and deformation parameters based on the generalized Hoek-Brown and Mohr-Coulomb failure criteria. The GSI can be estimated using standard chart and field observations of rock mass blockiness and discontinuity surface conditions. The GSI value gives a numerical representation of the overall geotechnical quality of the rock mass. In this study, we propose a method to determine the GSI quantitatively using photographic images of in situ jointed rock mass with image processing technology, fractal theory and artificial neural network (ANN). We employ the GSI system to characterize the jointed rock mass around the working in a coal mine. The relative error between the proposed value and the given value in the GSI chart is less than 3.6%.

Keywords: jointed rock mass; geological strength index (GSI); image processing; fractal dimension; artificial neural network (ANN)

1. Introduction

Generally, knowledge on the mechanical properties of rock mass is a prerequisite for the numerical simulation and the design of the underground structure, opening-up of mineral deposits and mining processes.

Since the early 1990s, many scholars (e.g. Hoek and Brown, 1997; Hoek et al., 2005, 2008, 2013; Hoek and Marinos, 2007) have proposed a variety of methods to determine the strength and deformation parameters of rock mass using geological strength index (GSI). The standard GSI chart considers qualitatively the surface condition and blockiness of a rock mass, and is used to estimate a value between 0 and 100 representing the overall geotechnical quality of the rock mass (Fig. 1). The GSI approach has been modified over the years and applied to characterizing the mechanical properties of rock mass by many authors (e.g. Sonmez and Ulusay, 1999; Cai et al., 2004, 2007; Sonmez et al., 2004; Bridean, 2005; Marinos et al., 2006).

Quantifying estimates of GSI may provide a means of reducing inadvertent errors and inconsistencies by inexperienced practitioners in classifying a rock mass.

Bieniawski (1989) and Hoek and Brown (1997) suggested that GSI can be related to the modified rock mass quality index Q and rock mass rating (RMR), respectively. A recent paper by Hoek et al. (2013) proposed a method for quantifying GSI using the rock quality designation (RQD), the joint condition rating of the RMR system, and the joint condition factor ($JCond_{89}$) by Bieniawski (1989). Russo (2009) suggested a new approach for quantitative assessment of the GSI (Hoek et al., 1995) by means of the basic input parameters for the determination of the rock mass index (RMI), such as the elementary block volume and the joint conditions. A recent paper by Bertuzzi et al. (2016) provided data from four different rock masses to extend the case history proposed by Hoek et al. (2013). The correlation between the GSI qualitatively assessed from the standard GSI chart and the quantified GSI was found to be fair for the datasets from the four rock masses.

Akin (2013) estimated the GSI value using the back analysis method with shear strength parameters of a failure surface in heavily jointed rock masses on a slope. The shear strength parameters of a failure surface under a specific normal stress can be determined using the material constants of the Hoek-Brown failure criterion (m_b and s) as a function of the GSI value. Also, Tajdus (2010) proposed a back analysis method of the surface subsidence, which is based on the uniaxial compressive strength R_c of rock samples, as well as mining and geological conditions, to determine the GSI values of a rock mass disturbed by underground exploitation.

In recent years, several authors such as Han et al. (2014), Poulsen et al. (2015) and Wang et al. (2015a) have also suggested many methods to determine the strength and deformation parameters of rock mass using GSI. All of the above-mentioned papers focused on quantifying the GSI chart to facilitate use of the system especially by inexperienced practitioners.

Many researchers (e.g. Crosta, 1997; Castleman, 2002; Hadjigeorgiou et al., 2003; Lemy and Hadjigeorgiou, 2003; Lato et al., 2009) have investigated digital face mapping as a practical tool to characterize rock masses, which can significantly reduce the time required in the field and avoid exposure to potentially unsafe conditions.

The digital rock mass rating (DRMR) developed by Monte (2004) uses basic image processing procedures and calculations to estimate a classification rating from digital images of rock masses. The rating system incorporates fracture information collected from a discontinuity trace map (e.g. length, spacing, large-scale, roughness, rock bridge percentage, and








GEOLOGICAL STRENGTH INDEX FOR JOINTED ROCKS	SURFACE CONDITIONS				
	VERY GOOD	GOOD	FAIR	POOR	VERY POOR
STRUCTURE	DECREASING SURFACE QUALITY →				
 DECREASING INTERLOCKING OF ROCK PIECES ↓	 INTACT OR MASSIVE—intact rock specimens or massive in situ rock with few widely spaced discontinuities	90			
	 BLOCKY—well interlocked undisturbed rock mass consisting of cubical blocks formed by three intersecting discontinuity sets	80	70		
	 VERY BLOCKY—interlocked, partially disturbed mass with multi-faceted angular blocks formed by 4 or more joint sets		60		
	 BLOCKY/DISTURBED/SEAMY—folded with angular blocks formed by many intersecting discontinuity sets. Persistence of bedding planes or schistosity			40	
	 DISINTERATED—poorly interlocked, heavily broken rock mass with mixture of angular and rounded rock pieces				20
	 LAMINATED/SHEARED—Lack of blockiness due to close spacing of weak schistosity or shear planes				10

Fig. 1. Chart for determining GSI of jointed rock mass (Hoek and Brown, 1997).

The best outcomes can be achieved only by collaboration between experienced engineering geologists and geotechnical engineers.

* Corresponding author. E-mail address: hkui66107@star-co.net.kp

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات