

Accepted Manuscript

Elastic-plastic analysis of functionally graded bars under torsional loading

George C. Tsiatas, Nick G. Babouskos

PII: S0263-8223(16)32511-9

DOI: <http://dx.doi.org/10.1016/j.compstruct.2017.05.044>

Reference: COST 8553

To appear in: *Composite Structures*

Received Date: 11 November 2016

Revised Date: 12 April 2017

Accepted Date: 17 May 2017



Please cite this article as: Tsiatas, G.C., Babouskos, N.G., Elastic-plastic analysis of functionally graded bars under torsional loading, *Composite Structures* (2017), doi: <http://dx.doi.org/10.1016/j.compstruct.2017.05.044>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Elastic-plastic analysis of functionally graded bars under torsional loading

George C. Tsiatas^a and Nick G. Babouskos^b

^aCorresponding author. e-mail: gtsiatas@math.upatras.gr, Department of Mathematics, University of Patras, Rio, GR-26504, Greece

^be-mail: babouskosn@yahoo.gr, School of Civil Engineering, National Technical University of Athens, Athens, GR-15773, Greece

Keywords: Functionally graded materials, Non-homogeneous media, Elastic-plastic, Torsion.

Abstract. In this paper a new integral equation solution to the elastic-plastic problem of functionally graded bars under torsional loading is presented. The formulation is general in the sense that it can be applied to an arbitrary cross-section made of any type of elastoplastic material. In material science the Functionally Graded Material (FGM) is a non-homogeneous composite which performs as a single-phase material, by unifying the best properties of its constituent phase material. The nonlinear elastic-plastic behavior is treated by employing the deformation theory of plasticity. According to this theory, the material constants are assumed variable within the cross section, and are updated through an iterative process so as the equivalent stress and strain at each point coincide with the uniaxial material curve. In this investigation a new straightforward nonlinear procedure is introduced in the deformation theory of plasticity which simplifies the solution method. At each iteration step, the warping function is obtained by solving the torsion problem of a non-homogeneous isotropic bar using the Boundary Element Method (BEM) in conjunction with the Analog Equation Method (AEM). Without restricting the generality, the FGM material is comprised of a ceramic phase and a metal phase. The ceramic is assumed to behave linearly elastic, whereas the metal is modeled as an elastic – linear hardening material. Furthermore, the TTO homogenization scheme for estimating the effective properties of the two-phase FGM was adopted. Several bars with various cross-sections and material types are analyzed, in order to validate the proposed model and exemplify its salient features. Moreover, useful conclusion are drawn from the elastic-plastic behavior of functionally graded bars under torsional loading.

1. Introduction

In this paper a new integral equation solution to the elastic-plastic problem of functionally

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات