



## Hybrid protection algorithms based on game theory in multi-domain optical networks

Lei Guo<sup>a,b,c</sup>, Jingjing Wu<sup>a,\*</sup>, Weigang Hou<sup>a</sup>, Yejun Liu<sup>a</sup>, Lincong Zhang<sup>a</sup>, Hongming Li<sup>a</sup>

<sup>a</sup> College of Information Science and Engineering, Northeastern University, Shenyang 110819, China

<sup>b</sup> State Key Laboratory of Advanced Optical Communication Systems and Networks, Peking University, Beijing 100871, China

<sup>c</sup> Department of Computing, Hong Kong Polytechnic University, Kowloon, Hong Kong, China

### ARTICLE INFO

#### Article history:

Received 5 April 2011

Revised 15 June 2011

Available online 23 July 2011

#### Keywords:

Multi-domain optical network

Survivability

Game theory

Bacterial colony optimization

Heuristic

### ABSTRACT

With the network size increasing, the optical backbone is divided into multiple domains and each domain has its own network operator and management policy. At the same time, the failures in optical network may lead to a huge data loss since each wavelength carries a lot of traffic. Therefore, the survivability in multi-domain optical network is very important. However, existing survivable algorithms can achieve only the unilateral optimization for profit of either users or network operators. Then, they cannot well find the double-win optimal solution with considering economic factors for both users and network operators. Thus, in this paper we develop the multi-domain network model with involving multiple Quality of Service (QoS) parameters. After presenting the link evaluation approach based on fuzzy mathematics, we propose the game model to find the optimal solution to maximize the user's utility, the network operator's utility, and the joint utility of user and network operator. Since the problem of finding double-win optimal solution is NP-complete, we propose two new hybrid protection algorithms, Intra-domain Sub-path Protection (ISP) algorithm and Inter-domain End-to-end Protection (IEP) algorithm. In ISP and IEP, the hybrid protection means that the intelligent algorithm based on Bacterial Colony Optimization (BCO) and the heuristic algorithm are used to solve the survivability in intra-domain routing and inter-domain routing, respectively. Simulation results show that ISP and IEP have the similar comprehensive utility. In addition, ISP has better resource utilization efficiency, lower blocking probability, and higher network operator's utility, while IEP has better user's utility.

© 2011 Elsevier Inc. All rights reserved.

### 1. Introduction

In Wavelength-Division-Multiplexing (WDM) optical networks, the failures may lead to a huge data loss since each wavelength carries a lot of traffic [1]. Therefore, survivability including protection method and restoration method to ensure the service continuity and quality in the network is very important [2,3]. In protection method [4,5], the backup resources are pre-assigned to the primary resources during the connection setup, and then the traffic carried by the primary resources can be directly switched to the backup resources if the failures occur. In restoration method [6], the backup resources are dynamically searched to carry the traffic if the primary resources are unavailable due to the failures. Current works mostly focused on the protection method since it has faster failure recovery to satisfy a lot of real-time demands in the network [4–6].

At the same time, with the network size increasing, the current optical backbone actually is divided into multiple domains and each domain has its own network operator and management policy for independent routing and failure recovery. Since the development of multi-domain optical networks is the trend of next-generation intelligent optical networks, the survivability in multi-domain optical networks becomes an important and challenging issue [7,8]. Compared to single-domain network, the survivability in multi-domain network is more difficult since the network information of multi-domains is not accurate for searching the primary and backup resources. The reason for this is that each domain distributes only the partial information to other domains due to the constraints of network security, scalability, etc. In addition, the inter-domain failure recovery needs the cooperation among different domains that also increases the difficulty of survivability in multi-domain network.

In order to solve the survivability in multi-domain optical network, the authors in Ref. [9] proposed a path protection algorithm to address the issues of inter-domain routing and single-link failure protection based on the Full Mesh Abstracted (FMA) virtual topology [10]. In Ref. [11], the authors presented a sub-path

\* Corresponding author. Address: P.O. Box 365, College of Information Science and Engineering, Northeastern University, Shenyang 110819, China. Fax: +86 024 83687758.

E-mail address: haveball@163.com (J. Wu).

protection algorithm, in which each demand will be firstly assigned to an end-to-end inter-domain working path, then the working path will be separated to multiple working sub-paths based on the different domain ranges traversed by the working path, and finally each working sub-path will be assigned to a link-disjoint backup sub-path in the same domain. In Ref. [12], the authors proposed a differentiated protection scheme where different domains can use the different protection strategies, such as shared protection and dedicated protection. In Ref. [13], the authors presented a multi-domain p-cycles protection based on the limited information. In Ref. [14], the authors developed a multi-domain Hamiltonian cycle protection, in which a global Hamiltonian cycle protects the inter-domain failures in the multi-domain network and multiple local Hamiltonian cycles protect the intra-domain failures in each single-domain network. In Ref. [15], the authors proposed the segment-shared protection algorithm for dynamic connections in multi-domain optical mesh networks. In Ref. [16], the authors considered the graph partitioning and devised the multi-domain survivable algorithm.

In multi-domain network, there are multiple independent network operators and multiple independent users. On the one hand, the network operators will compete with each other to pursue the individual maximal profit by providing the limited resources to attract more users. On the other hand, the users will expect to obtain higher Quality of Service (QoS) from the network operators by paying less cost. Therefore, the interdependence and conflict of interest exist between different network operators and users. However, the existing survivable algorithms and schemes [9–16] in multi-domain optical network considered only the engineering and technology issues to assign the network resources to the users with assuming the cooperation between users and network operators. Therefore, they all ignored the practical and important issue that is related with the economical factor and profit. Thus, these existing algorithms and schemes can achieve only the unilateral optimization for profit of either users or network operators, and they cannot well find the double-win optimal solution for both users and network operators.

Although the authors in Refs. [17–21] studied the routing problem based on game theory with considering the economical factor and profit for both users and network operators, they focused on only the theoretical analysis for pricing strategy for single-domain network and they did not study the survivability in multi-domain network. In Ref. [22], although the authors developed an inter-domain routing based on game theory in multi-domain optical network, they neither address the survivability nor solve the double-win optimal solution for both users and network operators. Therefore, the survivability with economical factor and profit for both users and network operators in multi-domain optical network is still an open and challenging issue which motivates our work.

In this paper, we develop the logical topology model with considering the QoS parameters of delay, bit error rate (BER) and the number of available wavelengths based on FMA scheme for multi-domain optical network. Then, we present the link pricing method for physical and logical links, respectively. Since both network operators and users need to compute their own utilities to measure their own profits, we propose the link evaluation approach based on fuzzy mathematics. Further, we present the game model to find the optimal solution to maximize the user's utility, the network operator's utility and the joint utility of user and network operator based on the QoS requirements of each demand for achieving the double-win. Since the problem of finding the optimal double-win solution is NP-complete, we propose two novel hybrid protection algorithms, Intra-domain Sub-path Protection (ISP) algorithm and Inter-domain End-to-end Protection (IEP) algorithm, based on our proposed game model. The hybrid protection means that the intelligent algorithm based on Bacterial Colony Optimization

(BCO) [23] and the heuristic algorithm are used to solve the survivability in intra-domain routing and inter-domain routing, respectively. In ISP, we allocate an end-to-end inter-domain working path for each demand, and then we calculate a link-disjoint backup sub-path for each intra-domain working sub-path. In IEP, we allocate two end-to-end inter-domain paths for each demand, one is working path and the other one is backup path. Simulation results show that the two algorithms have the similar comprehensive utility. In addition, ISP has better resource utilization efficiency, lower blocking probability and higher network operator's utility, while IEP has better user's utility.

To the best of our knowledge, the work in this paper is the first study addressing the survivability based on game theory with considering the economic factors in multi-domain optical network. The rest of this paper is organized as follows: Section 2 is the problem statement; Section 3 presents the link evaluation approach; Section 4 proposes the game model; Section 5 describes the BCO routing algorithm; Section 6 develops the heuristic routing algorithm; Section 7 is for simulation and analysis; Section 7 concludes this paper.

## 2. Problem statement

### 2.1. Network model

A given multi-domain optical network is represented by  $G(G^i(V^i, L^i), L)$ ,  $1 \leq i \leq D$ , where  $L$  denotes the set of inter-links among different domains,  $G^i(V^i, L^i)$  denotes the topology of domain  $i$ ,  $V^i$  denotes the set of intra-nodes in domain  $i$ ,  $L^i$  denotes the set of intra-links in domain  $i$  and  $D$  denotes the number of domains. Since the intra-links and inter-links are all fibers, we assume that they have the same parameters; that is, each fiber link  $l$  has the following parameters:

- $W$ : Set of wavelengths on each link and  $|W|$  is the number of wavelengths to satisfy  $|W| = f_l + w_l + r_l$ , where  $f_l$  is the number of free wavelengths,  $w_l$  is the number of wavelengths assigned to working paths and  $r_l$  is the number of wavelengths reserved for backup paths.
- $del_l$ : Delay of link  $l$ .
- $ber_l$ : Bit error rate of link  $l$ .
- $\lambda_l$ : Available wavelength vector of link  $l$ ; if the  $n^{\text{th}}$  wavelength is available, then  $\lambda_l(n) = 1$ ; otherwise,  $\lambda_l(n) = 0$ .
- $c_l$ : Initial cost of link  $l$  and it is determined by production cost.
- $\theta_l$ : Wavelength availability of link  $l$  and it is written as  $\theta_l = f_l/|W|$  that is the ratio of free wavelengths to the total wavelengths.

### 2.2. User's demand

The user's demand refers to the network resources provided by network operator to user and the fees paid by user to network operator in each process of communication. We define the user's demand for a unicast as:

$$R(v_s, v_d, w_l, \Delta del, \Delta ber, pay_{wm}, pay_{pm}) \quad (1)$$

where  $v_s$  is the source node;  $v_d$  is the destination node;  $w_l$  is the number of wavelengths required by user;  $\Delta del$  is the delay required by user and it is confined by the range  $[del_{\min}, del_{\max}]$ , that is, the total delay on the communication path should be less than  $del_{\max}$ ;  $\Delta ber$  is the BER required by user and it is confined by the range  $[ber_{\min}, ber_{\max}]$ , that is, the total BER on the communication path should be less than  $ber_{\max}$ ;  $pay_{wm}$  is the maximum expense the user would like to pay for the working path;  $pay_{pm}$  is the maximum expense the user would like to pay for the backup path. If the fees charged by network operator on the working path and

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات