

Accepted Manuscript

Research papers

A risk-based multi-objective model for optimal placement of sensors in water distribution system

Sareh S. Naserizade, Mohammad Reza Nikoo, Hossein Montaseri

PII: S0022-1694(17)30846-6
DOI: <https://doi.org/10.1016/j.jhydrol.2017.12.028>
Reference: HYDROL 22439

To appear in: *Journal of Hydrology*

Received Date: 30 June 2017
Revised Date: 7 December 2017
Accepted Date: 8 December 2017

Please cite this article as: Naserizade, S.S., Nikoo, M.R., Montaseri, H., A risk-based multi-objective model for optimal placement of sensors in water distribution system, *Journal of Hydrology* (2017), doi: <https://doi.org/10.1016/j.jhydrol.2017.12.028>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



A risk-based multi-objective model for optimal placement of sensors in**water distribution system****Sareh S. Naserizade^a, Mohammad Reza Nikoo^{b,*}, Hossein Montaseri^c**^a Research Assistant, School of Engineering, Department of Civil Engineering, Yasouj University, Yasouj, Iran;Email: sara.naseryi@gmail.com^{b,*} Assistant professor, School of Engineering, Department of Civil and Environmental Engineering, Shiraz University, Shiraz, Iran, Phone: +98-71-36133497, Email: nikoo@shirazu.ac.ir (Corresponding Author)^c Assistant professor, School of Engineering, Department of Civil Engineering, Yasouj University, Yasouj, Iran; Email: hmontaseri@gmail.com**Abstract**

In this study, a new stochastic model based on Conditional Value at Risk (CVaR) and multi-objective optimization methods is developed for optimal placement of sensors in water distribution system (WDS). This model determines minimization of risk which is caused by simultaneous multi-point contamination injection in WDS using CVaR approach. The CVaR considers uncertainties of contamination injection in the form of probability distribution function and calculates low-probability extreme events. In this approach, extreme losses occur at tail of the losses distribution function. Four-objective optimization model based on NSGA-II algorithm is developed to minimize losses of contamination injection (by CVaR of affected population and detection time) and also minimize the two other main criteria of optimal placement of sensors including probability of undetected events and cost. Finally, to determine the best solution, Preference Ranking Organization METHod for Enrichment Evaluation (PROMETHEE), as a subgroup of Multi Criteria Decision Making (MCDM) approach, is utilized to rank the alternatives on the trade-off curve among objective functions. Also sensitivity analysis is done to investigate the importance of each criterion on PROMETHEE results considering three relative weighting scenarios. The effectiveness of

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات