


Accepted Manuscript

Synergy assessment of hybrid reinforcements in concrete

Sabrina Vantadori, Andrea Carpinteri, Li-Ping Guo, Camilla Ronchei, Andrea Zanichelli



PII: S1359-8368(18)30526-2

DOI: [10.1016/j.compositesb.2018.04.020](https://doi.org/10.1016/j.compositesb.2018.04.020)

Reference: JCOMB 5628

To appear in: *Composites Part B*

Received Date: 13 February 2018

Revised Date: 5 April 2018

Accepted Date: 7 April 2018

Please cite this article as: Vantadori S, Carpinteri A, Guo L-P, Ronchei C, Zanichelli A, Synergy assessment of hybrid reinforcements in concrete, *Composites Part B* (2018), doi: 10.1016/j.compositesb.2018.04.020.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

SYNERGY ASSESSMENT OF HYBRID REINFORCEMENTS IN CONCRETE

Sabrina VANTADORI*, Andrea CARPINTERI*, Li-Ping GUO**,
Camilla RONCHEI*, Andrea ZANICHELLI*

*Dept. of Engineering and Architecture, University of Parma,
Parco Area delle Scienze 181/A, 43124 Parma, Italy

**School of Materials Science and Engineering, Southeast University,
211189 Nanjing, China

Corresponding Author: Sabrina Vantadori sabrina.vantadori@unipr.it

ABSTRACT

The present paper is devoted to the assessment of synergy due to the combined use of metallic and synthetic fibres in concrete matrix. Such an evaluation is performed both at first cracking stage by computing fracture toughness, and at post-peak stage by determining two toughness indexes. The results from experimental three-point bending tests on concrete specimens reinforced with copper-coated steel fibres and polypropylene fibres are employed for such computations. The novelty of this research work is that the Mixed Mode loading effect occurring at crack tip is taken into account when computing fracture toughness. Plain concrete specimens and specimens reinforced with only one type of fibres are experimentally and analytically examined for comparison.

KEYWORDS: concrete, fibres, fracture toughness, hybrid reinforcement, synergy, toughness index

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات