

Accepted Manuscript

Title: Contrasting Energy Efficiency in Various Ceramic Sintering Processes

Authors: Damoon Sohrabi Baba Heidary, Michael Lanagan, Clive A. Randall



PII: S0955-2219(17)30683-0
DOI: <https://doi.org/10.1016/j.jeurceramsoc.2017.10.015>
Reference: JECS 11502

To appear in: *Journal of the European Ceramic Society*

Received date: 21-2-2017
Revised date: 5-10-2017
Accepted date: 5-10-2017

Please cite this article as: Sohrabi Baba Heidary Damoon, Lanagan Michael, Randall Clive A. Contrasting Energy Efficiency in Various Ceramic Sintering Processes. *Journal of The European Ceramic Society* <https://doi.org/10.1016/j.jeurceramsoc.2017.10.015>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Contrasting Energy Efficiency in Various Ceramic Sintering Processes

Damoon Sohrabi Baba Heidary*, Michael Lanagan, and Clive A. Randall

Center for Dielectrics and Piezoelectrics, Materials Research Institute, the Pennsylvania State University, University Park, PA 16802, USA

Abstract

Regarding the recent energy costs and environmental concerns, energy efficient and sustainable manufacturing processes have become important topics. In this paper, a number of novel sintering methods were reviewed to illustrate their potential to reduce energy consumption during ceramic processing. Three approaches: adding sintering aid, increasing heating rate, and applying electric field on the reduction of the energy consumption were considered, and the underlying mechanism in each approach was explored. Next, the laser sintering that is utilized in additive manufacturing approaches and the new Cold Sintering Process (CSP) were introduced as potential techniques for the further improvement of energy efficiency. Since the need of furnaces was eliminated in these latter techniques, their heat dissipation during sintering would significantly decline. For example, it was demonstrated that the energy consumption for BaTiO₃ powder can decrease from 2800 kJ/g for conventional techniques to 30 kJ/g for CSP. A simple parameter, “Normalized Excess Energy”, was used as a first order approximation to compare the energy merit in the different sintering techniques.

Keywords: Energy efficiency; Ceramics; Sintering;

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات