

## Accepted Manuscript

A comparison of quality control methods for scratch detection on polished metal surfaces

Karlis Agris Gross, Janis Lungevics, Juris Zavickis, Liene Pluduma

PII: S0263-2241(17)30793-5  
DOI: <https://doi.org/10.1016/j.measurement.2017.12.022>  
Reference: MEASUR 5153

To appear in: *Measurement*

Received Date: 15 November 2016  
Revised Date: 12 December 2017  
Accepted Date: 13 December 2017

Please cite this article as: K. Agris Gross, J. Lungevics, J. Zavickis, L. Pluduma, A comparison of quality control methods for scratch detection on polished metal surfaces, *Measurement* (2017), doi: <https://doi.org/10.1016/j.measurement.2017.12.022>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



## A comparison of quality control methods for scratch detection on polished metal surfaces

Karlis Agris Gross, Janis Lungevics, Juris Zavickis, Liene Pluduma

Faculty of Materials Science and Applied Chemistry, Riga Technical University, Latvia

**Abstract:** Scratch detection and the location of the scratch on the surface is important in the quality control of multilayered, functional and polished surfaces. Visual examination in good lighting conditions has been previously used to detect scratches, but interest to see finer scratches and their location should consider use of the optical microscope, and compare it with other imaging methods at the same magnification. Stainless steel was polished, scratched and then one specific location analyzed at the same magnification for all methods to determine the level of scratch detection. Atomic force microscopy as the technique with a higher resolution was used to determine the mean depth of every scratch as a reference. An image was then taken with the different techniques and the number of visible scratches counted. Profilometry did not clearly identify scratches due to limitation of the 2  $\mu\text{m}$  probe size. Light microscopy provided the fastest and most appropriate technique for quality control, detecting 70% of the scratches. Scanning electron microscopy only showed 35% of the scratches at the same magnification, but provides a good 2-D image of the scratch and the resulting metal pile-up.

Keywords: polished surfaces, scratch, scratch detection, microscopy, quality control

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات