

Accepted Manuscript

Multiphysics topology optimization for piezoelectric acoustic focuser

Gil Ho Yoon, Hyunggyu Choi, Shin Hur

PII: S0045-7825(17)30753-3
DOI: <https://doi.org/10.1016/j.cma.2017.12.002>
Reference: CMA 11694

To appear in: *Comput. Methods Appl. Mech. Engrg.*

Received date: 2 June 2017
Revised date: 30 November 2017
Accepted date: 1 December 2017

Please cite this article as: G.H. Yoon, H. Choi, S. Hur, Multiphysics topology optimization for piezoelectric acoustic focuser, *Comput. Methods Appl. Mech. Engrg.* (2017), <https://doi.org/10.1016/j.cma.2017.12.002>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Multiphysics topology optimization for piezoelectric acoustic focuser

Gil Ho Yoon*¹, Hyunggyu Choi¹, Shin Hur²

School of Mechanical Engineering, Hanyang University, Seoul, Korea

Korea Institute of Machinery & Materials 156 Gajeongbuk-Ro, Yuseong-Gu, Daejeon, Korea

Abstract

The application of piezoelectric materials allows many advantages such as reducing the number of parts and manufacturing cost of a mechanical system. Despite these merits, the performance predictions and optimization of piezoelectric-material-based devices are challenging because of the mutual coupling between electricity and mechanics. The analysis and the optimization become more challenging when acoustics are to be coupled with piezoelectric-material-based devices. In the present study, the mutual couplings among electric, mechanics, and acoustics are simulated and its applications for the topology optimization of an acoustic energy focuser are presented. Owing to the local optima issue, some blurred and unsuccessful layouts are obtained. To overcome this issue and impose the manufacturing constraint, a modified morphology density filter is also developed. With the presented approach, it is possible to determine some optimized piezoelectric rings to focus acoustic energy. Compared with the existing design methods, some better designs in terms of objective value can be obtained by the present approach.

Keywords: Topology optimization, Piezoelectric material, SIMP approach, Acoustic focuser, Manufacturing constraint

* Correspondence to Associate Professor Gil Ho Yoon, E-mail: ghy@hanyang.ac.kr or gilho.yoon@gmail.com.

School of Mechanical Engineering, Hanyang University, Seoul, Korea

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات