

Accepted Manuscript

Inhibition of calcium carbonate crystal growth by organic additives using the constant composition method in conditions of recirculating cooling circuits

Chhim Norinda, Kharbachi Chams, Neveux Thibaut, Bouteleux Céline, Teychene Sébastien, Biscans Béatrice

PII: S0022-0248(17)30141-0

DOI: <http://dx.doi.org/10.1016/j.jcrysgro.2017.03.004>

Reference: CRY 24079

To appear in: *Journal of Crystal Growth*



Please cite this article as: C. Norinda, K. Chams, N. Thibaut, B. Céline, T. Sébastien, B. Béatrice, Inhibition of calcium carbonate crystal growth by organic additives using the constant composition method in conditions of recirculating cooling circuits, *Journal of Crystal Growth* (2017), doi: <http://dx.doi.org/10.1016/j.jcrysgro.2017.03.004>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Inhibition of calcium carbonate crystal growth by organic additives using the constant composition method in conditions of recirculating cooling circuits

CHHIM Norinda^{a,b}, KHARBACHI Chams^b, NEVEUX Thibaut^a, BOUTELEUX Céline^a, TEYCHENE Sébastien^b, BISCANS Béatrice^b

^aEDF Lab Chatou, 6 quai Watier 78401 Chatou Cedex, France

^bLaboratoire de Génie Chimique, Université de Toulouse, CNRS, INPT, UPS, Toulouse, France
4 allée Emile Monso CS84234, 31432 Toulouse, France

ABSTRACT

The cooling circuits used in power plants are subject to mineral crystallization which can cause scaling on the surfaces of equipment and construction materials reducing their heat exchange efficiency. Precipitated calcium carbonate is the predominant mineral scale commonly observed in cooling systems. Supersaturation is the key parameter controlling the nucleation and growth of calcite in these systems. The present work focuses on the precipitation of calcite using the constant composition method at constant supersaturation, through controlled addition of reactants to a semi-batch crystallizer, in order to maintain constant solution pH. The determination of the thermodynamic driving force (supersaturation) was based on the relevant chemical equilibria, total alkalinity and calculation of the activity coefficients. Calcite crystallization rates were derived from the experiments performed at supersaturation levels similar to those found in industrial station cooling circuits. Several types of seeds particles were added into the aqueous solution to mimic natural river water conditions in terms of suspended particulate matters content, typically: calcite, silica or illite particles. The effect of citric and copolycarboxylic additive inhibitors added to the aqueous solution was studied. The calcium carbonate growth rate was reduced by 38.6 % in the presence of the citric additive and a reduction of 92.7 % was observed when the copolycarboxylic additive was used under identical experimental conditions. These results are explained by the location of the adsorbed inhibitor at the crystal surface and by the degree of chemical bonding to the surface.

Keywords: A1.precipitation, A1.constant supersaturation ratio, A1.scaling, A1.additives, B1.calcium carbonate

متن کامل مقاله

دریافت فوری ←

ISIArticles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات