## Accepted Manuscript

Physical simulation study on the hydraulic fracture propagation of coalbed methane well

Caifang Wu, Xiaoyang Zhang, Meng Wang, Longgang Zhou, Wei Jiang

PII: S0926-9851(17)30679-1

DOI: https://doi.org/10.1016/j.jappgeo.2018.01.030

Reference: APPGEO 3429


To appear in:

Received date: 18 July 2017

Revised date: 21 December 2017 Accepted date: 31 January 2018

Please cite this article as: Caifang Wu, Xiaoyang Zhang, Meng Wang, Longgang Zhou, Wei Jiang, Physical simulation study on the hydraulic fracture propagation of coalbed methane well. The address for the corresponding author was captured as affiliation for all authors. Please check if appropriate. Appgeo(2017), https://doi.org/10.1016/j.jappgeo.2018.01.030

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



## CCEPTED MANUSCRIPT

Physical Simulation Study on the Hydraulic Fracture Propagation

of Coalbed Methane Well

Caifang Wu<sup>1,2</sup>, Xiaoyang Zhang<sup>1,2,3</sup>, Meng Wang<sup>1,2</sup>, Longgang Zhou<sup>1,2</sup> and Wei Jiang<sup>1,2</sup>

<sup>1</sup>Key Laboratory of Coalbed Methane Resource and Reservoir Formation Process, Ministry of Education,

Xuzhou 221008, People's Republic of China

<sup>2</sup> School of Resources and Geosciences, China University of Mining & Technology, Xuzhou 221008,

People's Republic of China

<sup>3</sup> Corresponding author

E-mail: zhanglsyr@cumt.edu.cn

Abstract

As the most widely used technique to modify reservoirs in the exploitation of unconventional natural gas,

hydraulic fracturing could effectively raise the production of CBM wells. To study the propagation rules of

hydraulic fractures, analyze the fracture morphology, and obtain the controlling factors, a physical simulation

experiment was conducted with a tri-axial hydraulic fracturing test system. In this experiment, the fracturing

sample -- including the roof, the floor, and the surrounding rock -- was prepared from coal and similar

materials, and the whole fracturing process was monitored by an acoustic emission instrument. The results

demonstrated that the number of hydraulic fractures in coal is considerably higher than that observed in other

parts, and the fracture morphology was complex. Vertical fractures were interwoven with horizontal fractures,

forming a connected network. With the injection of fracturing fluid, a new hydraulic fracture was produced

and it extended along the preexisting fractures. The fracture propagation was a discontinuous, dynamic

process. Furthermore, in-situ stress plays a key role in fracture propagation, causing the fractures to extend in

a direction perpendicular to the minimum principal stress. To a certain extent, the different mechanical

## دريافت فورى ب

## ISIArticles مرجع مقالات تخصصی ایران

- ✔ امكان دانلود نسخه تمام متن مقالات انگليسي
  - ✓ امكان دانلود نسخه ترجمه شده مقالات
    - ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
  - ✓ امكان دانلود رايگان ۲ صفحه اول هر مقاله
  - ✔ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
    - ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات