

## Accepted Manuscript

### Measuring Acoustic Resonator Properties Using Volume Modification Devices and Numerical Optimization

Patrick Thomas Weber, David Edwin Walrath

PII: S0263-2241(17)30381-0

DOI: <http://dx.doi.org/10.1016/j.measurement.2017.05.073>

Reference: MEASUR 4799

To appear in: *Measurement*

Received Date: 24 February 2016

Accepted Date: 31 May 2017

Please cite this article as: P.T. Weber, D.E. Walrath, Measuring Acoustic Resonator Properties Using Volume Modification Devices and Numerical Optimization, *Measurement* (2017), doi: <http://dx.doi.org/10.1016/j.measurement.2017.05.073>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



# Measuring Acoustic Resonator Properties Using Volume Modification Devices and Numerical Optimization

Patrick Thomas Weber\*, David Edwin Walrath

*Department of Mechanical Engineering (Dept. 3295)  
University of Wyoming  
1000 E. University Ave.  
Laramie, Wyoming 82071*

---

## Abstract

In this paper, a method for measuring resonator chamber volume and acoustic neck length by modifying chamber volume is presented. This method measures frequency changes caused by volume changes to determine core system volume and resonator neck length. Experimental measurements and data are presented along with measurement statistics. This method reduces the need for accurate resonator geometry knowledge by instead using external volume modification devices, where geometry is much easier to control.

This method serves to enhance existing volume measurement methods such that sources of inaccuracy are minimized. Results indicate that resonator volume and acoustic neck diameter can be measured with reasonable accuracy (less than the 1% error associated with liquid-volume measurement techniques) when neck diameter and change in volume are known in advance.

*Keywords:* Resonance, Signal Processing, Measurement Systems, Volume, Effective Length, System Dynamics

---

## 1. Introduction

In many industries, internal volume is a critical parameter in process control. For example, in internal combustion engine thermodynamics, fuel efficiency, performance, and combustion are acutely sensitive to combustion chamber volume [1]. In biomedical applications such as artificial hearts, chamber blood volume can indicate cardiovascular system blood flow rates [2]. Unfortunately, measuring internal volume with accuracy can be difficult, which inhibits reductions in process control variations and tolerances.

Helmholtz resonance is a phenomenon where a gas-filled cavity will audibly resonate in the presence of other acoustic noise sources [3]. In Helmholtz resonance-based systems, modeling natural resonant frequency with accuracy can be difficult due to non-linear

---

\*Corresponding author

*Email addresses:* pweber2@uwyo.edu (Patrick Thomas Weber), walrath@uwyo.edu (David Edwin Walrath)

*Preprint submitted to Journal of the International Measurement Confederation*

*June 1, 2017*

متن کامل مقاله

دریافت فوری ←

**ISI**Articles

مرجع مقالات تخصصی ایران

- ✓ امکان دانلود نسخه تمام متن مقالات انگلیسی
- ✓ امکان دانلود نسخه ترجمه شده مقالات
- ✓ پذیرش سفارش ترجمه تخصصی
- ✓ امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
- ✓ امکان دانلود رایگان ۲ صفحه اول هر مقاله
- ✓ امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
- ✓ دانلود فوری مقاله پس از پرداخت آنلاین
- ✓ پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات