Accepted Manuscript

Research Paper

Hole-bottom freezing technique based on phase change heat transfer for gashydrates sampling: Efficiency optimization of refrigeration change of phase

Youhong Sun, Yuan Wang, Wei Guo, Rui Jia, Guanghua Chen, Pengyu Zhang

PII:	\$1359-4311(17)31247-4
DOI:	https://doi.org/10.1016/j.applthermaleng.2017.11.012
Reference:	ATE 11382
To appear in:	Applied Thermal Engineering
Received Date:	22 February 2017
Revised Date:	19 July 2017
Accepted Date:	3 November 2017



Please cite this article as: Y. Sun, Y. Wang, W. Guo, R. Jia, G. Chen, P. Zhang, Hole-bottom freezing technique based on phase change heat transfer for gas-hydrates sampling: Efficiency optimization of refrigeration change of phase, *Applied Thermal Engineering* (2017), doi: https://doi.org/10.1016/j.applthermaleng.2017.11.012

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

Hole-bottom freezing technique based on phase change heat transfer for

gas-hydrates sampling: Efficiency optimization of refrigeration change of

phase

Youhong Sun^{a,b}, Yuan Wang^{a,b}, Wei Guo^{a,b*}, Rui Jia^{a,b*}, Guanghua Chen^{a,b}, Pengyu

Zhang^{a,b}

^a College of Construction Engineering, Jilin University, No.968 Ximinzhu Rd., Chaoyang District,

Changchun 130026, CHINA

^b Key Laboratory of Ministry of Land and Resources on Complicated Conditions Drilling

Technology, No.968 Ximinzhu Rd., Chaoyang District, Changchun 130026, CHINA

Keywords: gas hydrates sampling, phase change, heat transfer, efficiency optimization, gasification refrigeration.

Abstract: Coring is the key to the exploration and exploitation of natural gas hydrate. Less than 60% of gas-hydrate cores can be retrieved by the existing pressure preservation technique because of mechanical valve sealing failures. To solve this problem, a freezing sampling method was proposed. The cold-alcohol was formed by dry ice gasification refrigeration to reduce the temperature of the hydrate core in the drilling-hole and to prevent the decomposition of the gas-hydrates. However, gasification efficiency of dry ice in the narrow sampler's internal space is notably low, and the cryogenic alcohol cannot meet the requirements of the frozen hydrate core. In this paper, three different structures of the mixing chamber are proposed to improve the

دريافت فورى 🛶 متن كامل مقاله

- امکان دانلود نسخه تمام متن مقالات انگلیسی
 امکان دانلود نسخه ترجمه شده مقالات
 پذیرش سفارش ترجمه تخصصی
 امکان جستجو در آرشیو جامعی از صدها موضوع و هزاران مقاله
 امکان دانلود رایگان ۲ صفحه اول هر مقاله
 امکان پرداخت اینترنتی با کلیه کارت های عضو شتاب
 دانلود فوری مقاله پس از پرداخت آنلاین
 پشتیبانی کامل خرید با بهره مندی از سیستم هوشمند رهگیری سفارشات
- ISIArticles مرجع مقالات تخصصی ایران